

Fuse modular terminal block - PT 4-FSI/F-LED 70 - 1058965

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Fuse modular terminal block, nominal current: 10 A, nom. voltage: 70 V



COMPLETE™

Key Commercial Data

Packing unit	1
GTIN	 4 055626 703152
GTIN	4055626703152
Custom tariff number	85369010

Technical data

General

Maximum current with single arrangement	15 A
Voltage LED	70 V
Current LED	1.8 mA
Maximum load current	15 A (with 6 mm ² conductor cross section, rigid)
Nominal current I _N	10 A
Nominal voltage U _N	70 V
Open side panel	Yes

Ambient conditions

Ambient temperature (operation)	-60 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C (For a short time, not exceeding 24 h, -60 to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C

Fuse modular terminal block - PT 4-FSI/F-LED 70 - 1058965

Technical data

Ambient conditions

Ambient temperature (actuation)	-5 °C ... 70 °C
---------------------------------	-----------------

Connection data

Conductor cross section flexible max.	6 mm ²
---------------------------------------	-------------------

Classifications

eCl@ss

eCl@ss 10.0.1	27141116
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116
eCl@ss 9.0	27141116

ETIM

ETIM 5.0	EC000899
ETIM 6.0	EC000899
ETIM 7.0	EC000899

Approvals

Approvals

Approvals

CSA / EAC / EAC


Ex Approvals

Approval details

Fuse modular terminal block - PT 4-FSI/F-LED 70 - 1058965

Approvals

CSA		http://www.csagroup.org/services-industries/product-listing/	13631
	B	C	
Nominal voltage UN	300 V	300 V	
Nominal current IN	15 A	15 A	
mm ² /AWG/kcmil	24-10	24-10	

EAC		RU C- DE.AI30.B.01102
-----	---	--------------------------

EAC		RU C- DE.BL08.B.00644
-----	---	--------------------------