

Ferrule - A 16 -32 - 1090633

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ferrule, length: 32 mm, color: silver

Your advantages

- ✓ The dimensions of the ferrules conform to DIN 46228-1
- ✓ The ferrules without plastic sleeve are made from soft tin-plated electrolytic copper

Key Commercial Data

| | |
|------------------------|---------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 250 pc |
| GTIN | 4 055626 900896 |
| GTIN | 4055626900896 |
| Custom tariff number | 85369010 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--|--------|
| Length (b) | 32 mm |
| Maximum stripping length | 32 mm |
| Inner dimension of the insulating collar (d) | 7.5 mm |
| Ferrule diameter | 5.8 mm |
| Sleeve wall thickness | 0.2 mm |

Ambient conditions

| | |
|------------------------|--------|
| Short-term temperature | 120 °C |
|------------------------|--------|

Ferrule - A 16 -32 - 1090633

Technical data

Ambient conditions

| | |
|----------------------------|--------|
| Max. permanent temperature | 105 °C |
|----------------------------|--------|

General

| | |
|--------------------|---|
| Color | silver |
| Material | CU-DHP |
| Coating | tin-plated (galvanic) |
| Conductor category | Stranded conductors, class 2, 5, 6 / B, C, K, M |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27400201 |
| eCl@ss 8.0 | 27400201 |
| eCl@ss 9.0 | 27400201 |

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC000005 |
| ETIM 6.0 | EC000005 |
| ETIM 7.0 | EC000005 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

| | | | |
|-----------|--|---|---------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E488001 |
|-----------|--|---|---------|

Ferrule - A 16 -32 - 1090633

Approvals

| | | | |
|------------|--|---|---------|
| cUL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E488001 |
|------------|--|---|---------|

| | | | |
|--------------|--|--|--|
| cULus Listed | | | |
|--------------|--|--|--|

Accessories

Accessories

Crimping tool

Crimping pliers - CRIMPFOX 25R - 1212039



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 10 mm² ... 25 mm², lateral entry, WM crimp