

Multimeter - TESTFOX M-1 - 1212209

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Digital multimeter, for DC and AC voltage measurements, DC and AC measurements, and feed-through, resistance, frequency, temperature, and capacitance measurements

Your advantages

- ✓ Digital multimeters offer remarkable technology and impressive quality
- ✓ The devices are extremely versatile
- ✓ Independently tested and approved according to applicable IEC/EN 61010 standards by the certification institute
- ✓ The devices can be used for voltages of up to 600 V category III or 1000 V category II
- ✓ They provide professional service engineers and operating engineers with a higher level of protection, thereby ensuring maximum safety during work
- ✓ TESTFOX M-1 can also be used to measure DC and AC currents, capacitance, and frequencies, as well as temperatures within the range of -20°C to +800°C
- ✓ Phase voltages can be detected precisely thanks to the audible and red light signals
- ✓ Cable breaks and faulty lamps in exposed cables can be traced from the phase feed side right to the point of interruption
- ✓ Suitable for measuring AC voltages and resistance as well as testing continuity and diodes

Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 449786 |
| GTIN | 4046356449786 |
| Weight per Piece (excluding packing) | 580.000 g |
| Custom tariff number | 90303100 |
| Country of origin | Taiwan |

Technical data

Dimensions

Multimeter - TESTFOX M-1 - 1212209

Technical data

Dimensions

| | |
|------------|--------|
| Length (b) | 156 mm |
| Width (a) | 74 mm |
| Height (c) | 44 mm |

Ambient conditions

| | |
|---------------------------------|----------------|
| Ambient temperature (operation) | 0 °C ... 50 °C |
| Degree of protection | IP30 |

General

| | |
|--------------------|------------------------------------|
| Color | black |
| Power supply | 2 x micro battery 1.5 V, LR03, AAA |
| Measuring category | CAT III 600 V / CAT II 1000 V |
| Test certificate | IEC/EN 61010-1, DIN VDE 0411 |
| Display scope | 2000 digits |

Environmental Product Compliance

| | |
|---------------------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
| California Proposition 65 | Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27200301 |
| eCl@ss 4.0 | 27271100 |
| eCl@ss 4.1 | 27200300 |
| eCl@ss 5.0 | 27200300 |
| eCl@ss 5.1 | 27200300 |
| eCl@ss 6.0 | 27200300 |
| eCl@ss 7.0 | 27200301 |
| eCl@ss 8.0 | 27200301 |
| eCl@ss 9.0 | 27200301 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000069 |
| ETIM 4.0 | EC000069 |
| ETIM 5.0 | EC000069 |
| ETIM 6.0 | EC000069 |

Multimeter - TESTFOX M-1 - 1212209

Classifications

ETIM

| | |
|----------|----------|
| ETIM 7.0 | EC000069 |
|----------|----------|

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 41113630 |
| UNSPSC 18.0 | 41113630 |
| UNSPSC 19.0 | 41113630 |
| UNSPSC 20.0 | 41113630 |
| UNSPSC 21.0 | 41113630 |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|---------------|
| EAC |  | EAC-Zulassung |
|-----|---|---------------|
