


Adapter - SAC BIT M12-W14 - 1212513

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a hexagonal knurl wrench size of 14 mm, with 4 mm hexagonal drive

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 585767
GTIN	4046356585767
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	82079030
Country of origin	Germany

Technical data

General

Material	V4A
----------	-----

Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration
---------------------------	---

Classifications

eCl@ss

eCl@ss 10.0.1	21044290
eCl@ss 4.0	21040200
eCl@ss 4.1	21040200
eCl@ss 5.0	21040200
eCl@ss 5.1	21040200
eCl@ss 6.0	21040200

Adapter - SAC BIT M12-W14 - 1212513

Classifications

eCl@ss

eCl@ss 7.0	21045003
eCl@ss 8.0	21045003
eCl@ss 9.0	21044290

ETIM

ETIM 4.0	EC002498
ETIM 5.0	EC000149
ETIM 6.0	EC000149
ETIM 7.0	EC000149

UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27113201
UNSPSC 18.0	27111701
UNSPSC 19.0	27111701
UNSPSC 20.0	27111701
UNSPSC 21.0	27111701

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	---	---------------

Adapter - SAC BIT M12-W14 - 1212513

Accessories

Additional products

Torque screwdriver - TSD 04 SAC - 1208429



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

Torque screwdriver - TSD-M 1,2NM - 1212224



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits
