

## Philips screwdriver - SF-PH 1-80 - 1212559

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Screwdriver, PH crosshead (lasered), uninsulated, size: PH 1 x 80, 2-component grip, with non-slip grip

### Your advantages

- Screwdrivers for Phillips screws with Pozidriv and Phillips Recess screw head

### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 589949
GTIN	4046356589949
Weight per Piece (excluding packing)	62.000 g
Custom tariff number	82054000
Country of origin	Czech Republic

### Technical data

#### Dimensions

Length (b)	178 mm
Width (a)	33 mm
Blade width	4.5 mm
Blade height	80 mm
Wrench size	0 mm

#### General

Type	Phillips
	straight
Material	alloyed tool steel
Test standard	DIN ISO 8764-1

### Standards and Regulations

# Philips screwdriver - SF-PH 1-80 - 1212559

## Technical data

### Standards and Regulations

Test standard	DIN ISO 8764-1
---------------	----------------

### Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration
---------------------------	---

## Drawings

Pictogram



# Philips screwdriver - SF-PH 1-80 - 1212559

## Classifications

### eCl@ss

eCl@ss 10.0.1	21040406
eCl@ss 4.0	21040400
eCl@ss 4.1	21040400
eCl@ss 5.0	21040400
eCl@ss 5.1	21040400
eCl@ss 6.0	21040400
eCl@ss 7.0	21040406
eCl@ss 8.0	21040406
eCl@ss 9.0	21040406

### ETIM

ETIM 4.0	EC000144
ETIM 5.0	EC000144
ETIM 6.0	EC000144
ETIM 7.0	EC000144

### UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701
UNSPSC 18.0	27111701
UNSPSC 19.0	27111701
UNSPSC 20.0	27111701
UNSPSC 21.0	27111701

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

## Philips screwdriver - SF-PH 1-80 - 1212559

### Approvals

#### Approval details

EAC		RU C- DE.AI30.B.01750
-----	---	--------------------------