

# Torque screwdriver - TSD 08 SAC - 1212597

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Torque screw driver with preset torque of 0.8 Nm, with 4 mm hexagon for accommodating SAC bits, two-component handle with non-slip grip

The figure shows the TSD 04 SAC version

#### Your advantages

- For the TSD-M... torque screwdrivers, the torque can be custom-set

## **Key Commercial Data**

Packing unit	1 pc
GTIN	4 046356 590716
GTIN	4046356590716
Weight per Piece (excluding packing)	100.000 g
Custom tariff number	82054000
Country of origin	Czech Republic

#### Technical data

#### **Dimensions**

Length (b)	205 mm
Width (a)	37 mm
Blade thickness	0 mm
Blade width	0 mm
Blade height	100 mm

#### General

Color	black
Туре	Hexagonal SW4



# Torque screwdriver - TSD 08 SAC - 1212597

## Technical data

## General

Material	alloyed tool steel
Environmental Product Compliance	
California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

## Classifications

## eCl@ss

eCl@ss 10.0.1	21040417
eCl@ss 4.0	21040200
eCl@ss 4.1	21040200
eCl@ss 5.0	21040200
eCl@ss 5.1	21040200
eCl@ss 6.0	21040200
eCl@ss 7.0	21040417
eCl@ss 8.0	21040417
eCl@ss 9.0	21040417

#### **ETIM**

ETIM 4.0	EC000149
ETIM 5.0	EC002132
ETIM 6.0	EC002132
ETIM 7.0	EC002132

#### UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

## Approvals

## Approvals

Approvals

EAC



## Torque screwdriver - TSD 08 SAC - 1212597

## Approvals

Ex Approvals

Approval details

EAC

EHE

RU x-DE.xx08.B.02974

#### Accessories

#### Accessories

Screwdriver tools

Tool - SAC BIT QUICKON-W13 - 1212033



Nut for assembling pressure nuts with 13 mm wrench size, for 4 mm hexagonal drive

Tool - SACC BIT M12-D20 - 1208445



Nut for assembling M12 connectors for assembly with a knurl diameter of 20 mm, for 4 mm hexagonal drive

Tool - SAC BIT MIN-D25 - 1212512



Nut for assembling 7/8" connectors with a knurl diameter of 25 mm, with 4 mm hexagonal drive

Phoenix Contact 2020 @ - all rights reserved http://www.phoenixcontact.com