

FO patch cable - FOC-LC:A-LC:A-GZ03/2 - 1400622

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled FO cable, zip cord cable, multi-mode fiberglass 50/125 μm , OM4, plug: LC/LC, degree of protection: IP20, for installation in cable ducts or control cabinets, length: 2 m


Your advantages

- ✔ Multi-mode patch cable for indoor installation
- ✔ Ideal for use in distributor systems and for connecting termination devices
- ✔ All components satisfy UL 94, V0
- ✔ 2.8 mm single elements made from halogen-free and flame-retardant material
- ✔ Interferometer tests at every stage of the certification process
- ✔ Excellent mechanical and optical properties
- ✔ Satisfies optical and mechanical industry standards
- ✔ Connector with UPC polishing for optimum attenuation values
- ✔ Low-bend fiber
- ✔ Insertion loss ≤ 0.5 dB
- ✔ Return loss ≥ 35 dB
- ✔ Comprehensively tested according to IEC 61753-122-2 and IEC 61753-1 Cat. C
- ✔ Temperature fluctuation test according to IEC 61300-2-1
- ✔ Vibration test according to IEC 61300-2-1
- ✔ Tensile strength of the cable connection according to IEC 61300-2-5

RoHS

IP20

Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 734875 |
| GTIN | 4046356734875 |
| Weight per Piece (excluding packing) | 40.000 g |
| Custom tariff number | 85447000 |

FO patch cable - FOC-LC:A-LC:A-GZ03/2 - 1400622

| | |
|-------------------|---------|
| Country of origin | Germany |
|-------------------|---------|

Technical data

Mechanical characteristics

| | |
|--|--------|
| Insertion/withdrawal cycles | ≥ 500 |
| Weight | 45.5 g |
| Flammability rating according to UL 94 | V0 |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -10 °C ... 60 °C |
| Ambient temperature (assembly) | -5 °C ... 50 °C |
| Ambient temperature (storage/transport) | -10 °C ... 60 °C |

Electrical characteristics

| | |
|------------------|---------|
| Lateral strength | 60 N/cm |
|------------------|---------|

Standards and Regulations

| | |
|--|------------------------------|
| Flame resistance | yes |
| Halogen-free | complying with IEC 60754-1/2 |
| Flammability rating according to UL 94 | V0 |

Line characteristics

| | |
|---|---|
| Type of cable | Zip cord |
| Cable type | Fiberglass |
| Cable abbreviation | I-V(ZN)H |
| External cable diameter | 2.8 mm (Zip cord) |
| Wire colors | - |
| External sheath, color | Violet |
| Wavelength | 850, 1300 nm |
| Transmission medium | Multi-mode fiberglass |
| Number of fibers | 2 |
| Fiber type | Multi-mode 50/125 µm fiberglass |
| Fiber | 50/125 µm |
| Cable, attenuation | 2.5 dB/km (at 850 nm), 0.7 dB/km (at 1300 nm) |
| Outer sheath, material | LSZH |
| Cable weight | 15.80 kg/km |
| Smallest bending radius, fixed installation | 15 mm |
| Smallest bending radius, movable installation | 30 mm |
| Tensile strength short-term/long-term | 600 N |
| cable layer type | Indoors |
| Flame resistance | yes |
| Halogen-free | complying with IEC 60754-1/2 |

FO patch cable - FOC-LC:A-LC:A-GZ03/2 - 1400622

Technical data

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27061003 |
| eCl@ss 4.0 | 27260700 |
| eCl@ss 4.1 | 27260700 |
| eCl@ss 5.0 | 27260700 |
| eCl@ss 5.1 | 27260700 |
| eCl@ss 6.0 | 27260700 |
| eCl@ss 7.0 | 27440309 |
| eCl@ss 8.0 | 27061003 |
| eCl@ss 9.0 | 27061003 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC001121 |
| ETIM 4.0 | EC000034 |
| ETIM 5.0 | EC001263 |
| ETIM 6.0 | EC001263 |
| ETIM 7.0 | EC001263 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11 | 31261501 |
| UNSPSC 12.01 | 31261501 |
| UNSPSC 13.2 | 26121607 |
| UNSPSC 18.0 | 26121607 |
| UNSPSC 19.0 | 26121607 |
| UNSPSC 20.0 | 26121607 |
| UNSPSC 21.0 | 26121607 |

Approvals

Approvals

FO patch cable - FOC-LC:A-LC:A-GZ03/2 - 1400622

Approvals


Approvals

UL Listed / EAC

Ex Approvals

Approval details

| | | | |
|-----------|---|---|------------------|
| UL Listed |  | http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm | E308814-20070105 |
|-----------|---|---|------------------|

| | | | |
|-----|---|--|---------|
| EAC |  | | B.01742 |
|-----|---|--|---------|
