

## FO connecting cable - FOC-PN-B-1000/M12-C/M12-C/2 - 1408870

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled FO cable, round cable, 980/1000 µm POF fiber, M12 FO to M12 FO, for installation inside buildings, length: 2 m

POF cable, assembled with M12 connectors to M12

### Product Description


POF cable, assembled with M12 connectors to M12

### Your advantages

- ✓ 2.2 mm individual wires made from extremely hard-wearing polyamide (PA)
- ✓ Assembled patch cable with test report
- ✓ M12-OPTIC with recessed ferrules to protect against damage
- ✓ optimized polishing for even better attenuation values
- ✓ Rugged polyurethane (PUR) outer sheath
- ✓ Pin connector pattern in accordance with DIN/IEC 61754-27
- ✓ Included in PROFINET planning guideline (v1.14)
- ✓ Robust connector, IP65/IP67
- ✓ Can be used in 10/100 Mbps Ethernet systems



### Key Commercial Data

Packing unit	1
GTIN	 4 055626 070629
GTIN	4055626070629
Custom tariff number	85447000

### Technical data

### Standards and Regulations

# FO connecting cable - FOC-PN-B-1000/M12-C/M12-C/2 - 1408870

## Technical data

### Standards and Regulations

Impact strength	2 Nm / 10 x
Flammability rating according to UL 94	V0

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Dimensional drawing



## Classifications

eCl@ss

eCl@ss 10.0.1	27061003
eCl@ss 4.0	27061000
eCl@ss 4.1	27061000
eCl@ss 5.0	27061000
eCl@ss 5.1	27061000
eCl@ss 8.0	27061003
eCl@ss 9.0	27061003

ETIM

ETIM 4.0	EC001263
ETIM 5.0	EC001263
ETIM 6.0	EC001263
ETIM 7.0	EC001263

# FO connecting cable - FOC-PN-B-1000/M12-C/M12-C/2 - 1408870

## Classifications

### UNSPSC

UNSPSC 13.2	26121607
UNSPSC 18.0	26121607
UNSPSC 19.0	26121607
UNSPSC 20.0	26121607
UNSPSC 21.0	26121607

## Accessories

### Accessories

#### Circular connectors (device side)

FO transceiver - FOC-M12-MNNA-TC-650 - 1416716



M12 FO transceiver, duplex, wavelength: 650 nm for 125 Mbps, for POF and PCF fiber, for PCB mounting, M16 fastening thread, with sealing cap, including I<sup>2</sup>C interface for transceiver monitoring and management

Fiber optic coupling - FOC-M12-BU/BU - 1416677



Fiber optics coupling M12, duplex, suitable for all fibers, with wall bracket, IP65 degree of protection

Fiber optic contact insert - FOC-M12-RS-POF - 1406421



Replacement ferrule set (10 pcs.) for M12 POF fiber optic connector (Order No. 1416606)

## Spare parts

## FO connecting cable - FOC-PN-B-1000/M12-C/M12-C/2 - 1408870

### Accessories

Fiber optic contact insert - FOC-M12-RS-POF - 1406421



Replacement ferrule set (10 pcs.) for M12 POF fiber optic connector (Order No. 1416606)