

## Fiber optic coupling - FOC-V06-D1PGY-S/SJBE4 - 1410050

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



SC-RJ coupling, IP65/67, duplex, can be used for GOF (multi-mode and single-mode), PCF, and polymer fiber types


SC-RJ field coupling

### Your advantages

- Permanent mounting is also an option
- Including covers to protect against environmental influences
- Can be used for all fiber types



### Key Commercial Data

Packing unit	1
GTIN	 4 046356 892704
GTIN	4046356892704
Custom tariff number	85366990

### Technical data

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Fiber optic coupling - FOC-V06-D1PGY-S/SJBE4 - 1410050

## Classifications

### eCl@ss

eCl@ss 10.0.1	27440304
eCl@ss 4.0	27060700
eCl@ss 4.1	27060700
eCl@ss 5.0	27400200
eCl@ss 5.1	27400200
eCl@ss 6.0	27400200
eCl@ss 7.0	27440304
eCl@ss 8.0	27440304
eCl@ss 9.0	27440304

### ETIM

ETIM 4.0	EC000516
ETIM 5.0	EC000516
ETIM 6.0	EC000516
ETIM 7.0	EC000516

### UNSPSC

UNSPSC 13.2	39121522
UNSPSC 18.0	39121522
UNSPSC 19.0	39121522
UNSPSC 20.0	39121522
UNSPSC 21.0	39121522

## Approvals

### Approvals

---

#### Approvals

EAC

---

#### Ex Approvals

---

### Approval details

EAC		B.01742
-----	---	---------

## Fiber optic coupling - FOC-V06-D1PGY-S/SJBE4 - 1410050

### Accessories

#### Accessories

#### Fiber optic connector (cable side)

#### FO connectors - VS-SCRJ-POF-FA-IP67 - 1657009



SC-RJ fiber optic connector, IP67, duplex, with fast connection technology, for polymer fiber 980/1000  $\mu\text{m}$ , for individual wire diameter 2.2 mm, for cable cross section 5.0 mm ... 8.5 mm

---

#### FO connectors - VS-SCRJ-HCS-FA-IP67 - 1657012



SC-RJ fiber optic connector, IP67, duplex, with fast connection technology, for PCF fiber 200/230  $\mu\text{m}$ , for individual wire diameter 2.9 mm, for cable cross section 5.0 mm ... 8.5 mm