

## FO connectors - FOC-C-SCRJ-GOF-SM-APC - 1412473

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



SC-RJ connector, with long bend protection, for single mode 9/125 µm, APC polishing (8°), green

### Product Description

SC-RJ connector, for wires 2.0 mm ... 3.0 mm in diameter, single mode 9/125 µm, APC polishing (8°)


The reusable connector is particularly suitable for quick and easy field connection, as there is no need for bonding and polishing.

### Your advantages

- ✓ suitable for quick and easy field assembly or repair
- ✓ No bonding or polishing
- ✓ Reusable connectors
- ✓ A real alternative to splicing
- ✓ Optimum attenuation values with easy assembly
- ✓ Long-term durability, thanks to the latest index matching gel
- ✓ the 8° fiber transition ensures optimum return loss (RL)
- ✓ meets IEC 61754-4 (SC) and FprEN 50377-17-1 (connectors for field assembly)
- ✓ Cleave technology
- ✓ Reusable connectors

RoHS IP20

### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| GTIN                                 | <br>4 046356 963886 |
| GTIN                                 | 4046356963886   |
| Weight per Piece (excluding packing) | 20.000 g  |
| Custom tariff number                 | 85367000  |
| Country of origin                    | Bulgaria  |

## FO connectors - FOC-C-SCRJ-GOF-SM-APC - 1412473

### Technical data

#### Mechanical characteristics

|  |                   |
|--|-------------------|
| Connection method                      | mechanical splice |
| Cable outlet                           | straight          |
| No. of cable outlets                   | 1                 |
| Locking type                           | Clip locking      |
| Weight                                 | 8.7 g             |
| Flammability rating according to UL 94 | V0                |

#### Ambient conditions

|                                 |                                |
|---------------------------------|--------------------------------|
| Ambient temperature (operation) | -10 °C ... 60 °C (IEC 61300-2) |
| Degree of protection            | IP20                           |

#### Electrical characteristics

|                    |         |
|--------------------|---------|
| Transmission speed | 10 Gbps |
|--------------------|---------|

#### Line characteristics

|                                       |  |
|---------------------------------------|--|
| Type of cable                         | For all common cable types                             |
| Cable type                            | Fiberglass   |
| Cable structure                       | Semi-loose compact wires (STB)                         |
| Number of fibers                      | 1  |
| Fiber type                            | Single-mode fiberglass                                 |
| Fiber                                 | GOF  |
| Attenuation                           | ≤ 0.5 dB ((95%) according to IEC 61300-3-34)           |
|                                       | ≤ 0.2 dB ((typical value) according to IEC 61300-3-34) |
| Tensile strength short-term/long-term | 70N (120s.) bei Aderdurchmesser >2 mm                  |
| cable layer type                      | Indoors  |

#### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

#### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 19170122 |
| eCl@ss 4.0    | 27260700 |
| eCl@ss 4.1    | 27260700 |

# FO connectors - FOC-C-SCRJ-GOF-SM-APC - 1412473

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.0 | 27260700 |
| eCl@ss 5.1 | 27260700 |
| eCl@ss 6.0 | 27180800 |
| eCl@ss 8.0 | 19170122 |
| eCl@ss 9.0 | 19170122 |

### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC001122 |
| ETIM 6.0 | EC001122 |
| ETIM 7.0 | EC001122 |

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 43223310 |
| UNSPSC 18.0 | 43223310 |
| UNSPSC 19.0 | 43223310 |
| UNSPSC 20.0 | 43223310 |
| UNSPSC 21.0 | 43223310 |

## Approvals

### Approvals

Approvals

EAC

Ex Approvals

### Approval details

|     |  |         |
|-----|--|---------|
| EAC |  | B.01742 |
|-----|--|---------|

## Accessories

### Accessories

## FO connectors - FOC-C-SCRJ-GOF-SM-APC - 1412473

### Accessories

FO accessories - FOC-TOOL-FERRULECLEANER-2.50 - 1407029



2.50 mm ferrule cleaner, for ST, SC, FC, E2000 (also APC), approx. 500 cleaning cycles

---

Tool set - FOC-TOOL-GOF KONF SET - 1411049



Tool set for GOF assembly

---

### Necessary add-on products

Tool set - FOC-TOOL-GOF KONF SET - 1411049



Tool set for GOF assembly

---