

Reducing adapter - A-INR-PG16/13-N-NS-S - 1415216

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing adapter, material: Brass, nickel-plated, connecting thread: Pg16, color: silver, with O-ring

Product Description

Reduced Pg16 to Pg13,5

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 055626 038599
GTIN	4055626038599
Weight per Piece (excluding packing)	8.000 g
Custom tariff number	74199990
Country of origin	Germany

Technical data

Dimensions

Length	9.5 mm
Length without connecting thread	3.5 mm
Connecting thread diameter	37.5 mm
Hexagon angular dimension	26.7 mm
Length of the connecting thread	6.5 mm

Ambient conditions

Degree of protection (IP)	IP68 (Depends on the screw connection used)
---------------------------	---

Reducing adapter - A-INR-PG16/13-N-NS-S - 1415216

Technical data

General

Material	Brass, nickel-plated
O-ring material	NBR
Outer thread	Pg16
Internal thread	Pg13,5
Color	silver

Standards and Regulations

Halogen-free	no
--------------	----


Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Reducing adapter - A-INR-PG16/13-N-NS-S - 1415216

Dimensional drawing



Dimensional drawing

Classifications

eCl@ss

eCl@ss 10.0.1	27440201
eCl@ss 4.0	27141200
eCl@ss 4.1	27141200
eCl@ss 5.0	27149100
eCl@ss 5.1	27149100

Reducing adapter - A-INR-PG16/13-N-NS-S - 1415216

Classifications

eCl@ss

eCl@ss 6.0	27149100
eCl@ss 7.0	27149109
eCl@ss 8.0	27149109
eCl@ss 9.0	27440201

ETIM

ETIM 5.0	EC000441
ETIM 6.0	EC002309
ETIM 7.0	EC002309

UNSPSC

UNSPSC 13.2	39121311
UNSPSC 18.0	31261501
UNSPSC 19.0	31261501
UNSPSC 20.0	31261501
UNSPSC 21.0	31261501