

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON B10 sleeve housing, for single locking latch, height: 72 mm, with 1 x Pg29 gland, straight cable outlet



# **Key Commercial Data**

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 0 4 6 3 5 6 6 9 5 4 3 5
GTIN	4046356695435
Weight per Piece (excluding packing)	210.000 g
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### **Dimensions**

Height	72 mm
Width	43 mm
Length	73 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C 125 °C

#### General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24		
Size	B10		



## Technical data

## General


Housing type	Sleeve housing	
Locking type	for single locking latch	
No. of cable outlets	1	
Cable outlet	straight	
Screw connection	none	
Type of the screw connection	1x Pg29	
Housing material	Aluminum die-cast	
Housing surface material	Powder-coated, gray	
Assembly instructions	For half and full screw connections	


## **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e		
	No hazardous substances above threshold values		

# Drawings

### Dimensional drawing





Dimensional drawing



# Classifications

## eCl@ss

eCl@ss 10.0.1	27440202
eCl@ss 4.0	27140800
eCl@ss 4.1	27140800
eCl@ss 5.0	27143400
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27440202
eCl@ss 8.0	27440202
eCl@ss 9.0	27440202

### **ETIM**

ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437
ETIM 6.0	EC000437
ETIM 7.0	EC000437

### **UNSPSC**

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261501
UNSPSC 18.0	31261501
UNSPSC 19.0	31261501
UNSPSC 20.0	31261501
UNSPSC 21.0	31261501

# Approvals

Approvals			
Approvals			
EAC / EAC			
Ex Approvals			

07/01/2020 Page 3 / 5



## Approvals

Approval details

EAC RU C-DE.Al30.B.01102

EAC RU C-DE.AI30.B.01102

#### Accessories

Accessories

Full screw connection

Cable gland - G-INS-PG29-M68N-PNES-GY - 1411146



Cable gland, cable gland material: PA, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver-gray RAL 7001

#### Cable gland - G-INS-PG29-M68N-NNES-S - 1411176



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver, with O-ring

#### Cable gland - G-INSEC-PG29-M68N-NNES-S - 1411201



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 18 mm  $\dots$  25 mm, shielding: yes, connecting thread: Pg29, color: silver, with O-ring

Plug for cable screw gland



## Accessories

Screw plug - HC-BS-PG29 - 1674532



Screw plug, material: Brass, nickel-plated, connecting thread: Pg29, color: silver

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com