

Crimp contact - SB-36KP003 - 1623384

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Crimp contact, turned, Single contact, contact diameter: 3.6 mm, crimp range: 4 mm² ... 6 mm²

The figure may differ depending on the connection area

Your advantages

- High tensile strength of the connection



Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|-----------------|
| Minimum order quantity | 20 pc |
| GTIN | 4 055626 195261 |
| GTIN | 4055626195261 |
| Weight per Piece (excluding packing) | 6.000 g |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

General

| Contact type | turned |
|-------------------|------------------|
| Contact diameter | 3.6 mm |
| Type of contact | Pin |
| Connection method | Crimp connection |



Crimp contact - SB-36KP003 - 1623384

Technical data

General


| Insertion/withdrawal cycles mechanical | 100 |
|--|--|
| Litz wire cross section min. | 4 mm² |
| Litz wire cross section max. | 6 mm² |
| Contact material | CuZn |
| Contact surface | Nickel-plated (Ni), with gold coating (Au) |

Environmental Product Compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Dimensional drawing



Classifications

eCl@ss

| eCl@ss 10.0.1 | 27440204 |
|---------------|----------|
| eCl@ss 4.0 | 27260700 |
| eCl@ss 4.1 | 27260700 |
| eCl@ss 5.0 | 27260700 |
| eCl@ss 5.1 | 27261200 |
| eCl@ss 6.0 | 27261200 |
| eCl@ss 7.0 | 27440204 |
| eCl@ss 8.0 | 27440204 |
| eCl@ss 9.0 | 27440204 |



Crimp contact - SB-36KP003 - 1623384

Classifications

ETIM

| ETIM 5.0 | EC000796 |
|----------|----------|
| ETIM 6.0 | EC000796 |
| ETIM 7.0 | EC000796 |

UNSPSC

| UNSPSC 13.2 | 39121522 |
|-------------|----------|
| UNSPSC 18.0 | 39121522 |
| UNSPSC 19.0 | 39121522 |
| UNSPSC 20.0 | 39121522 |
| UNSPSC 21.0 | 39121522 |

Accessories

Accessories

Crimping tool

Crimping pliers with digital display - SF-Z0026 - 1607454



Crimping pliers for turned crimp contacts Ø 2 mm / Ø 3.6 mm, litz wire cross section of 1.5 mm² ... 10 mm²

SB-Z0026 - 1624618



Locator for SF-Z0026 crimping pliers, for crimping turned M40 hybrid contacts, diameter of 3.6 mm, cross section of 2.5 mm 2 ... 6 mm 2

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com