

Terminal outlet - VS-TO-IW-2-F-9010 - 1653016

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Terminal outlet, flush-type mounting, IP20, two slots for contact inserts with the Freenet system

Your advantages

- ✔ Can be optionally equipped with copper and FO inserts
- ✔ Halogen free, according to DIN VDE 0472/815

RoHS IP20

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 962081
GTIN	4017918962081
Weight per Piece (excluding packing)	48.600 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Width	80 mm
Length	80 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	5 °C ... 55 °C

General data

Housing material	PC+ABS
------------------	--------

Terminal outlet - VS-TO-IW-2-F-9010 - 1653016

Technical data

General data

Degree of protection	IP20
Number of slots	2

Standards and Regulations


Flammability rating according to UL 94	HB
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Terminal outlet

Classifications

eCl@ss

eCl@ss 10.0.1	27440318
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700

Terminal outlet - VS-TO-IW-2-F-9010 - 1653016

Classifications

eCl@ss

eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440309
eCl@ss 8.0	27440318
eCl@ss 9.0	27440318

ETIM

ETIM 2.0	EC000764
ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC002597
ETIM 6.0	EC002597
ETIM 7.0	EC002597

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501
UNSPSC 18.0	31261501
UNSPSC 19.0	31261501
UNSPSC 20.0	31261501
UNSPSC 21.0	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

Terminal outlet - VS-TO-IW-2-F-9010 - 1653016

Approvals

EAC



B.01687

Accessories

Accessories

Female insert

RJ45 socket insert - VS-08-BU-RJ45-5-F/PK - 1652936



RJ45 socket insert, degree of protection: IP20, number of positions: 8, CAT5 (IEC 11801:2002), material: Copper alloy, connection method: IDC, connection cross section: AWG 24- 22

RJ45 coupling - CUC-F-D1ZNI-S/R4GCHP8 - 1086111



RJ45 coupling, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Zinc die-cast, connection method: 2x RJ45, Freenet design for use with IP67 panel mounting frame and terminal outlets

Fiber optics connector (device side)

Fiber optic coupling - VS-SCRJ-GOF-KU - 1654358



SC-RJ coupling insert, duplex, for VS-PP-19-1HE-16-F patch panel, VS-TO...F... terminal outlets, and VS-SI-FP-2F front plate, can be used for GOF (multi-mode and single mode), HCS, and polymer fiber types

Rectangular connector (device side)

Terminal outlet - VS-TO-IW-2-F-9010 - 1653016

Accessories

RJ45 socket insert - VS-08-BU-RJ45-5-F/BU - 1652952



RJ45 socket insert, for the Freenet system, CAT5e, 8-pos., shielded, socket on socket

Fiber optic coupling - FL MM PATCH COUPLER LC-LC - 2700312



Coupling, LC/LC, can be used for multi-mode glass fibers

Fiber optic coupling - FL SM PATCH COUPLER LC-LC - 2700313



Coupling, LC/LC, can be used for single mode glass fibers
