


RJ45 bending protection sleeve - VS-08-KS-H/GY - 1654743

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

RJ45 bend protection sleeve, for pin inserts VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, for cable cross section up to 7 mm, color: gray



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
GTIN	 4 017918 977801
GTIN	4017918977801
Weight per Piece (excluding packing)	2.200 g
Custom tariff number	39269097
Country of origin	China

Technical data

Mechanical characteristics

Maximum external conductor diameter	7 mm
Weight	2.13 g
Flammability rating according to UL 94	V0

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

Material data

Housing material	PA
Width	13.5 mm
Height	17 mm

RJ45 bending protection sleeve - VS-08-KS-H/GY - 1654743

Technical data

Material data

Length	29.5 mm
--------	---------

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



RJ45 bending protection sleeve

Classifications

eCl@ss

eCl@ss 10.0.1	27440212
eCl@ss 4.0	27140900
eCl@ss 4.1	27140900
eCl@ss 5.0	27140900

RJ45 bending protection sleeve - VS-08-KS-H/GY - 1654743

Classifications

eCl@ss

eCl@ss 5.1	27140900
eCl@ss 6.0	27140900
eCl@ss 7.0	27439224
eCl@ss 8.0	27440212
eCl@ss 9.0	27440212

ETIM

ETIM 2.0	EC000307
ETIM 3.0	EC001680
ETIM 4.0	EC001680
ETIM 5.0	EC001680
ETIM 6.0	EC001680
ETIM 7.0	EC001679

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

RJ45 bending protection sleeve - VS-08-KS-H/GY - 1654743

Accessories

Accessories

Male insert

RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716



RJ45 pin insert, CAT5, 8-pos., shielded, IDC connection technology, for 27 ... 26 AWG litz wires, with strain relief

RJ45 male insert - VS-08-ST-H21-RJ45 - 1652729



RJ45 male insert, CAT6, 8-pos., shielded, IDC displacement connection, for litz wire AWG 25 ... 24 and solid wires AWG 24, with strain relief
