

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



SC-RJ fiber optic connector, IP20, duplex, with fast connection technology, for polymer fiber 980/1000 μ m, for individual wire diameter 2.2 mm

SC-R.

Product Description

SC-RJ fiber optic connector, IP20, duplex, with fast connection technology, for polymer fiber 980/1000 µm, for individual wire diameter 2.2 mm

Your advantages

- ✓ No bonding or polishing
- ☑ Reusable connectors



Key Commercial Data

Packing unit	1 pc
GTIN	4 046356 028844
GTIN	4046356028844
Weight per Piece (excluding packing)	16.700 g
Custom tariff number	85367000
Country of origin	Germany

Technical data

Mechanical characteristics

Connection method	Push-Pull
Tightening torque max	1 Nm
Insertion/withdrawal cycles	≥ 100
Cable outlet	straight



Technical data

Mechanical characteristics

Weight	16.2 g
Flammability rating according to UL 94	V0

Ambient conditions

Ambient temperature (operation)	-25 °C 70 °C
Ambient temperature (assembly)	0 °C 50 °C
Ambient temperature (storage/transport)	-25 °C 70 °C
Degree of protection	IP20

Material data

Housing material	Zinc die-cast
Housing surface material	Nickel-plated
Width	16.5 mm
Height	11 mm
Length	83 mm

Optical characteristics

Attenuation	≤ 1.5 dB (Insertion attenuation)
-------------	----------------------------------

Standards and Regulations

Flame resistance	yes
Flammability rating according to UL 94	V0


Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings




Dimensional drawing



SC-RJ connector IP20

Schematic diagram



Classifications

eCl@ss

eCl@ss 10.0.1	19170122
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700



Classifications

eCl@ss

_	
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440309
eCl@ss 8.0	19170122
eCl@ss 9.0	19170122

ETIM

ETIM 2.0	EC000764
ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC001122
ETIM 6.0	EC001122
ETIM 7.0	EC001122

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	43223310
UNSPSC 18.0	43223310
UNSPSC 19.0	43223310
UNSPSC 20.0	43223310
UNSPSC 21.0	43223310

Approvals

Approvals
• •

Approvals

EAC

Ex Approvals

Approval details



Approvals

EAC

EHE

B.01742

Accessories

Accessories

Assembly tool

Tool set - TF-SCRJ-POF KONF SET - 1405246



SC-RJ cutting tool set, for polymer fiber, for field assembly of SC-RJ/IP20 and SC-RJ/IP67 push/pull connectors with fast connection technology, consisting of stripping tool, aramid scissors, SC-RJ cutting tool, microscope

FO accessories - VS-SCRJ-POF-KONFTOOL-POLISH - 1658820



SC-RJ polishing tool set, for polymer fiber, for field assembly of the SC-RJ connector (IP20/IP67) with fast connection technology, with stripping tool, diagonal cutter, aramid scissors, polishing materials, microscope, 2x SC-RJ connector IP20

FO accessories - VS-SCRJ-POF-POLISH - 1656673



Refilling set for VS-SC-RJ-POF-KONFTOOL-POLISH, consisting of two polishing discs and a polisher

FO accessories - WIREFOX-PN POF - 1405249



Sheath stripping tool, for polymer fiber



Accessories

Additional products

FO accessories - FOC-TOOL-FERRULECLEANER-2.50 - 1407029



2.50 mm ferrule cleaner, for ST, SC, FC, E2000 (also APC), approx. 500 cleaning cycles

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com