

## D-SUB pressure nut - VS-PG11 (3- 7) - 1688117


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB cap nut with line seal, for conductor diameter of 3 mm ... 7 mm, for sleeve housing VS-15-...



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
GTIN	 4 017918 182274
GTIN	4017918182274
Weight per Piece (excluding packing)	4.400 g
Custom tariff number	39269097
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Minimum external conductor diameter	3 mm
Maximum external conductor diameter	7 mm
Weight	4.48 g
Flammability rating according to UL 94	V0

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (assembly)	-20 °C ... 80 °C

#### Material data

Housing material	PA
------------------	----

# D-SUB pressure nut - VS-PG11 (3- 7) - 1688117

## Technical data

### Material data

Width	15 mm
Height	24.4 mm
Length	24.4 mm
Wrench size	22.00 mm

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Classifications

### eCl@ss

eCl@ss 10.0.1	27144420
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27069215
eCl@ss 8.0	27069215
eCl@ss 9.0	27144420

### ETIM

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000814
ETIM 6.0	EC000814
ETIM 7.0	EC000814

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31161514
UNSPSC 18.0	31161514
UNSPSC 19.0	31161514
UNSPSC 20.0	31161514

## D-SUB pressure nut - VS-PG11 (3- 7) - 1688117

### Classifications

#### UNSPSC

UNSPSC 21.0	31161514
-------------	----------