

D-SUB contact insert - VS-09-BU-DSUB/CAN - 1689051


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



D-SUB CAN-BUS contact insert, type 09, version: Socket



Key Commercial Data

Packing unit	1
GTIN	 4 017918 876814
GTIN	4017918876814
Custom tariff number	85369010

Technical data

Mechanical characteristics

Weight	11.92 g
Flammability rating according to UL 94	V0

Material data

Contact surface material	Tin-plated
Contact material	Copper alloy
Contact carrier material	PA
Width	24 mm
Height	59.8 mm
Length	104.65 mm

Electrical characteristics

GRP transmission properties	2
-----------------------------	---

Standards and Regulations

D-SUB contact insert - VS-09-BU-DSUB/CAN - 1689051

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27440217
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27261200
eCl@ss 6.0	27261200
eCl@ss 7.0	27440205
eCl@ss 8.0	27440205
eCl@ss 9.0	27440217

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438
ETIM 6.0	EC000438
ETIM 7.0	EC000438

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121421
UNSPSC 18.0	39121421
UNSPSC 19.0	39121421
UNSPSC 20.0	39121421
UNSPSC 21.0	39121421

D-SUB contact insert - VS-09-BU-DSUB/CAN - 1689051

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01687
-----	---	---------
