

RJ45 bending protection sleeve - VS-08-KS/GN - 1689226


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 bend protection sleeve, for pin insert VS-08-ST-RJ45, cable cross section up to 6 mm, color: green



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
GTIN	 4 017918 890575
GTIN	4017918890575
Weight per Piece (excluding packing)	6.330 g
Custom tariff number	39269097
Country of origin	United States

Technical data

Mechanical characteristics

Maximum external conductor diameter	6 mm
Weight	1.31 g
Flammability rating according to UL 94	V0

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

Material data

Housing material	PA
Width	12.5 mm
Height	12.5 mm

RJ45 bending protection sleeve - VS-08-KS/GN - 1689226

Technical data

Material data

Length	4.1 mm
--------	--------

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



RJ45 bending protection sleeve

Classifications

eCl@ss

eCl@ss 10.0.1	27440212
eCl@ss 4.0	27141200
eCl@ss 4.1	27141200
eCl@ss 5.0	27149100
eCl@ss 5.1	27149100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149110
eCl@ss 8.0	27440212
eCl@ss 9.0	27440212

RJ45 bending protection sleeve - VS-08-KS/GN - 1689226

Classifications

ETIM

ETIM 2.0	EC000241
ETIM 3.0	EC002040
ETIM 4.0	EC002040
ETIM 5.0	EC001680
ETIM 6.0	EC001680
ETIM 7.0	EC001679

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

Accessories

Accessories

Male insert

RJ45 bending protection sleeve - VS-08-KS/GN - 1689226

Accessories

RJ45 male insert - VS-08-ST-RJ45 - 1688573



RJ45 pin insert, CAT5e, 8-pos., shielded, IDC connection method, for litz wires AWG 26 and solid wires AWG 26 ... 24