

I/O module - IB ST 24 AO 4/EF - 2700839

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



INTERBUS-ST analog output module, 4 outputs, 0 - 10 V, ± 10 V, 0 - 20 mA, 4 - 20 mA, consisting of: terminal part with screw connection and module electronics



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4046356660501
Weight per Piece (excluding packing)	580.000 g
Custom tariff number	85389091
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	118 mm
Height	116 mm
Depth	117 mm

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

I/O module - IB ST 24 AO 4/EF - 2700839

Technical data

Ambient conditions

Air pressure (operation)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Degree of protection	IP20

General

Mounting type	DIN rail mounting
Net weight	585 g
Operating mode	Process data mode with 4 words
Diagnostics messages	Failure of the internal I/O supply I/O error message sent to the bus coupler
	F1 fuse failure I/O error message sent to the bus coupler
	I/O supply failure I/O error message sent to the bus coupler

Interfaces

Designation	ST local bus
No. of channels	2
Connection method	ST local bus connector
Transmission speed	500 kbps
Transmission physics	Copper

Power supply for module electronics

Connection method	ST local bus connector
Designation	Communications power
Supply voltage	9 V DC (from the ST local bus)
Current consumption	typ. 54 mA
	max. 80 mA
Power consumption	typ. 0.5 W
Designation	U_s
Voltage	24 V DC

Analog outputs

Number of outputs	4 (Voltage or current)
Connection technology	2, 3-conductor
Output name	Analog outputs
D/A conversion time	max. 1 ms (incl. slew rate)
D/A converter resolution	12 bit
Type of protection	Transient protection
Protective circuit/component	Suppressor diode
Representation of output values	16 bit two's complement
Current output signal	0 mA ... 20 mA (SF and SF4 mode)

I/O module - IB ST 24 AO 4/EF - 2700839

Technical data

Analog outputs

	4 mA ... 20 mA (Mode SF4)
Load/output load current output	to 500 Ω
Voltage output signal	-10 V ... 10 V (Mode BP)
	0 V ... 10 V (SF and SF4 mode)
Load/output load voltage output	> 2 kΩ

Electrical isolation

Test section	Bus/Outputs 500 V AC 50 Hz 1 min.
	Supply voltage/Outputs 500 V AC 50 Hz 1 min.
	Supply voltage/Ground conductor 500 V AC 50 Hz 1 min.
	I/O voltage/Ground conductor 500 V AC 50 Hz 1 min.

Standards and Regulations

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27242601
eCl@ss 4.0	27250300
eCl@ss 4.1	27250300
eCl@ss 5.0	27250300
eCl@ss 5.1	27242600
eCl@ss 6.0	27242600
eCl@ss 7.0	27242601
eCl@ss 8.0	27242601
eCl@ss 9.0	27242601

ETIM

ETIM 3.0	EC001596
ETIM 4.0	EC001596
ETIM 5.0	EC001596
ETIM 6.0	EC001596

I/O module - IB ST 24 AO 4/EF - 2700839

Classifications

ETIM

ETIM 7.0	EC001596
----------	----------

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	32151602
UNSPSC 18.0	32151602
UNSPSC 19.0	32151602
UNSPSC 20.0	32151602
UNSPSC 21.0	32151602

Accessories

Accessories

Bridge

Jumper - IB ST LBC - 2836492



Spare local bus cable, for INTERBUS-ST modules

Insertion bridge - EB 84 IB ST BU - 2836269



Insertion bridges, divisible, isolated comb spine, color blue, 84-pos.

Insertion bridge - EB 84 IB ST RD - 2836272



Insertion bridges, divisible, isolated comb spine, color red, 84-pos.

I/O module - IB ST 24 AO 4/EF - 2700839

Accessories

Fuse

Fuse - IBS TR5 0,4AT - 2753478



Replacement fuse, for INTERBUS-ST modules

Spare parts

Replacement electronics module - IB STME 24 AO 4/EF - 2701954



INTERBUS-ST analog output module, 4 outputs, 0 - 10 V, ± 10 V, 0 - 20 mA, 4 - 20 mA, comprising: Module electronics only
