

RJ45 connector - FL PLUG RJ45 GR/2 - 2744856

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


RJ45 connector, shielded, with bend protection sleeve, 2 pieces, gray for straight cables, for assembly on site. For connections that are not crossed, it is recommended that you use the connector set with gray bend protection sleeve.



The figure shows the version FL PLUG RJ45 GN/2

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 607579
GTIN	4017918607579
Weight per Piece (excluding packing)	18.710 g
Custom tariff number	85366990
Country of origin	United States

Technical data

Dimensions

Width	32.7 mm
Height	13.1 mm
Length	13.7 mm

Mechanical tests

Flammability rating according to UL 94	V0
--	----

General

Net weight	18.69 g
Housing material	Polycarbonate

RJ45 connector - FL PLUG RJ45 GR/2 - 2744856

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27440101
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440101
eCl@ss 8.0	27440101
eCl@ss 9.0	27440101

ETIM

ETIM 2.0	EC001423
ETIM 3.0	EC001423
ETIM 4.0	EC001423
ETIM 5.0	EC002636
ETIM 6.0	EC002636
ETIM 7.0	EC002636

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	39121409
UNSPSC 18.0	39121409
UNSPSC 19.0	39121409
UNSPSC 20.0	39121409
UNSPSC 21.0	39121409

RJ45 connector - FL PLUG RJ45 GR/2 - 2744856

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------
