

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The figure shows versions with a different no. of positions

Basic termination blocks with test connection on both sides and knife disconnection for NS 32 and NS 35/7.5 DIN rail, with end cover, for ST-REL..., ST-OV... and ST-OE... plugs, 3-pos.



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 017918 076832
GTIN	4017918076832
Weight per Piece (excluding packing)	62.940 g
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Width	20.8 mm
Height	86.5 mm
Depth	109.5 mm

General

Number of positions	3
Nominal voltage U _N	400 V (voltage is determined by the coupling connector.)
Nominal current I _N	16 A (current is determined by the coupling connector.)
Color	gray



Technical data

General

Insulating material	PA
Standards and Regulations	
Connection in acc. with standard CSA	
Environmental Product Compliance	
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27371603
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27371600
eCl@ss 5.1	27371600
eCl@ss 6.0	27371600
eCl@ss 7.0	27371603
eCl@ss 8.0	27371603
eCl@ss 9.0	27371603

ETIM

ETIM 2.0	EC001456
ETIM 3.0	EC001456
ETIM 4.0	EC001456
ETIM 5.0	EC001456
ETIM 6.0	EC001456
ETIM 7.0	EC001456

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39122326
UNSPSC 18.0	39122335
UNSPSC 19.0	39122335



Classifications

UNSPSC

UNSPSC 20.0	39122335
UNSPSC 21.0	39122335

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / DNV GL / cULus Recognized

Ex Approvals

Approval details

CSA	(3)	http://www.csagroup.org/services-industries/product-listing/ 13631		13631
Nominal voltage UN			300 V	
Nominal current IN			11 A	
mm²/AWG/kcmil			28-12	

UL Recognized	<i>7</i> .	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 60425		
Nominal voltage UN			300 V	
Nominal current IN			10 A	
mm²/AWG/kcmil			30-12	

cUL Recognized	.71	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILE E 604		FILE E 60425
Nominal voltage UN			300 V	
Nominal current IN			10 A	



Approvals

mm²/AWG/kcmil	30-12

RU C-DE.A*30.B.01742

DNV GL https://approvalfinder.dnvgl.com/ TAE00001CT

cULus Recognized

Accessories

Accessories

Bridge

Fixed bridge - FB-150 METER - 0201595



Cross connection rail, for fixed bridging of identical inputs and outputs, made of Cu, nickel-plated, 1 m long

Wire bridge - DB 50- 90 BU - 2821180

Wire bridge, color: blue

uuu

Wire bridge - DB 50- 90 BK - 2820916

Wire bridge, color: black





Accessories

Wire bridge - DB 50- 90 GY - 2820929



Basic terminal block - KB RELG 7 - 2961095



Fixed bridge, for cross connections, with screw, 7-pos.

Basic terminal block - KB RELG 4 - 2961082



Fixed bridge, for cross connections, with screw, 4-pos.

Jumper - KB RELG 3 - 2961079



Fixed bridge, for cross connections, with screw, 3-pos.

Jumper - KB RELG 2 - 2961066



Fixed bridge, for cross connections, with screw, 2-pos.

End block



Accessories

End clamp - E/UK - 1201442



End clamp, width: 9.5 mm, height: 35.3 mm, material: PA, length: 50.5 mm, Mounting on a DIN rail NS 32 or NS 35, color: gray

Mounting material

Screw - ZSR - 2303608



Screw

Test plug terminal block

Reducing plug - RPS - 0201647



Reducing plug, color: gray

Phoenix Contact 2020 @ - all rights reserved http://www.phoenixcontact.com