

Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cast front adapter with attached, halogen-free round cable and a 50-pos. socket strip injection-molded on both sides for the connection of Yokogawa controllers. Cable length: 8.0 m

Your advantages

- Molded connectors
- KS/AKB-compatible connectors on the module side
- Can be screwed on
- Lateral cable outlet of the I/O module

Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 882873 |
| GTIN | 4046356882873 |
| Custom tariff number | 85444290 |
| Country of origin | Germany |

Technical data

Note

| | |
|--------------|---|
| Type of note | Notes on operation |
| Note | No additional touch protection is required when using a SELV/PELV voltage (≤ 25 V AC or 60 V DC). |

Ambient conditions

| | |
|---|--|
| Ambient temperature (operation) | -40 °C ... 70 °C (fixed installation) |
| | -10 °C ... 70 °C (flexible installation) |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |

Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Technical data

Ambient conditions

| | |
|----------------------|--------------------------------|
| Maximum altitude | ≤ 2000 m |
| Degree of protection | IP20 |
| | ≥ IP54 (Installation location) |

General

| | |
|------------------------------------|-----------------------|
| Max. permissible operating voltage | 30 V DC |
| Max. permissible current | 500 mA (per path) |
| Mounting position | any |
| Nominal operating mode | 100% operating factor |

Standards and Regulations

| | |
|--------------------------|---------------------------------------|
| Flame resistance | IEC 60332-3-22 |
| | IEC 60332-1-2 |
| | VDE 0842, Part 332-1-2 |
| Resistance to oil | against occasional splashes |
| Gasoline resistance | against occasional splashes |
| Designation | Air clearances and creepage distances |
| Standards/regulations | DIN EN 50178 |
| Rated insulation voltage | 63 V |
| Rated surge voltage | 0.6 kV |
| Insulation | Functional insulation |
| Pollution degree | 2 |
| Overvoltage category | II |

Connection data

| | |
|-----------------------------|--------------------------------|
| Connection name | Control side |
| Connection method | Yokogawa, I/O cards compatible |
| Number of connections | 1 |
| Number of positions | 50 |
| Torque | 0.5 Nm (Screw connection) |
| Insertion/withdrawal cycles | > 50 |

Connection data 2

| | |
|-----------------------------|---------------------------|
| Connection name | Field level |
| Connection method | Yokogawa, KS compatible |
| Number of connections | 1 |
| Number of positions | 50 |
| Torque | 0.5 Nm (Screw connection) |
| Insertion/withdrawal cycles | > 50 |

Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Technical data

Cable

| | |
|---|--|
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| Single wire, cross section | 0.14 mm ² |
| Shielding | Tinned copper-braided shield, approx. 85% covering |
| Length of cable | 8 m |
| Outer sheath, material | Halogen-free sheath |
| External sheath, color | gray |
| Shielding | yes |
| Halogen-free cable | Yes |
| Cable insulation resistance | ≥ 20 MΩ/km |
| Cable resistance | ≤ 145 Ω/km |

Supported controller

| | |
|---------------------|--------------------------|
| Controller | YOKOGAWA CS3000 CentumVP |
| - suitable I/O card | ADV151 |
| | ADV551 |
| Controller | YOKOGAWA STARDOM |
| - suitable I/O card | NFDV151 |
| | NFDV551 |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Connection diagram

| 50-pos. connector to the I/O card | 50-pos. connector to the module | Wire color |
|---|---------------------------------------|---------------|
| 1 | 50 | black |
| 2 | 49 | brown |
| 3 | 48 | red |
| 4 | 47 | orange |
| 5 | 46 | yellow |
| 6 | 45 | green |
| 7 | 44 | blue |
| 8 | 43 | violet |
| 9 | 42 | gray |
| 10 | 41 | white |
| 11 | 40 | white-black |
| 12 | 39 | white-brown |
| 13 | 38 | white-red |
| 14 | 37 | white-orange |
| 15 | 36 | white-yellow |
| 16 | 35 | white-green |
| 17 | 34 | white-blue |
| 18 | 33 | white-violet |
| 19 | 32 | white-gray |
| 20 | 31 | brown-black |
| 21 | 30 | brown-red |
| 22 | 29 | brown-orange |
| 23 | 28 | brown-yellow |
| 24 | 27 | brown-green |
| 25 | 26 | brown-blue |
| 26 | 25 | brown-violet |
| 27 | 24 | brown-gray |
| 28 | 23 | brown-white |
| 29 | 22 | green-black |
| 30 | 21 | green-brown |
| 31 | 20 | green-red |
| 32 | 19 | green-orange |
| 33 | 18 | green-blue |
| 34 | 17 | green-violet |
| 35 | 16 | green-gray |
| 36 | 15 | green-white |
| 37 | 14 | yellow-black |
| 38 | 13 | yellow-brown |
| 39 | 12 | yellow-red |
| 40 | 11 | yellow-orange |
| 41 | 10 | yellow-blue |
| 42 | 9 | yellow-violet |
| 43 | 8 | yellow-gray |
| 44 | 7 | yellow-white |
| 45 | 6 | gray-black |
| 46 | 5 | gray-brown |
| 47 | 4 | gray-red |
| 48 | 3 | gray-orange |
| 49 | 2 | gray-yellow |
| 50 | 1 | gray-green |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27242292 |
| eCl@ss 4.0 | 27260700 |
| eCl@ss 4.1 | 27260700 |
| eCl@ss 5.0 | 27260700 |
| eCl@ss 5.1 | 27260700 |
| eCl@ss 6.0 | 27249200 |
| eCl@ss 7.0 | 27249290 |

Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 8.0 | 27249290 |
| eCl@ss 9.0 | 27242292 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC002584 |
| ETIM 5.0 | EC002584 |
| ETIM 6.0 | EC002584 |
| ETIM 7.0 | EC002584 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211810 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 32151601 |
| UNSPSC 18.0 | 32151601 |
| UNSPSC 19.0 | 32151601 |
| UNSPSC 20.0 | 32151601 |
| UNSPSC 21.0 | 32151601 |

Approvals


Approvals

Approvals

UL Listed / cUL Listed / EAC / cULus Listed

Ex Approvals

Approval details

| | | | |
|--------------------|---|---|---------------|
| UL Listed |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
| Nominal voltage UN | 125 V | | |
| Nominal current IN | 0.5 A | | |

Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Approvals

| | | | |
|--------------------|--|---|---------------|
| cUL Listed | | http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
| Nominal voltage UN | | 125 V | |
| Nominal current IN | | 0.5 A | |

| | | |
|-----|--|-------------------------|
| EAC | | RU C- DE.A*30.B00767 |
|-----|--|-------------------------|

| | |
|--------------|--|
| cULus Listed | |
|--------------|--|

Accessories

Accessories

Marker carrier cable

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable binders, cable diameter: > 5 mm, lettering field size: 20 mm x 8 mm

Spare parts

Screw set - VF-SCREW-YOKOGAWA/M3X18/DCS - 2902873



Replacement screw M3x18 for Yokogawa system cable, front adapter control side.

Front adapters - FLK 50-PA/EZ-DR/HF/KS/ 800/YUC - 2904745

Accessories

Screw set - VF-SCREW-YOKOGAWA/M4X25/KS - 2902874



Replacement screw M4x25 for Yokogawa system cable, module side.