

## Connection element - HV M12/1-VS 2 - 3049631


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Connection element, length: 62 mm, width: 25 mm, height: 4 mm, number of positions: 2, color: silver



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 313520
GTIN	4046356313520
Weight per Piece (excluding packing)	46.700 g
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Technical data

Color	silver
Material	Copper
Number of positions	2
Length	62 mm
Height	4 mm
Width	25 mm
Hole diameter	12.6 mm
Drill hole spacing	34 mm
Maximum load current	269 A

### Environmental Product Compliance

# Connection element - HV M12/1-VS 2 - 3049631

## Technical data

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27141190
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141190
eCl@ss 8.0	27141190
eCl@ss 9.0	27141190

### ETIM

ETIM 3.0	EC000483
ETIM 4.0	EC000483
ETIM 5.0	EC002848
ETIM 6.0	EC002848
ETIM 7.0	EC002848

### UNSPSC

UNSPSC 6.01	30211827
UNSPSC 7.0901	39121424
UNSPSC 11	39121424
UNSPSC 12.01	39121424
UNSPSC 13.2	39121410
UNSPSC 18.0	39121410
UNSPSC 19.0	39121410
UNSPSC 20.0	39121410
UNSPSC 21.0	39121410

## Approvals

### Approvals

---

## Connection element - HV M12/1-VS 2 - 3049631

### Approvals

Approvals

EAC

---

Ex Approvals

---

### Approval details

EAC		RU C- DE.A*30.B.01742
-----	---	--------------------------

---