

# Female test connector - PSBJ 6-T RD - 3070319

Female test connector, color: red

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

RoHS

## Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 046356 870849
GTIN	4046356870849
Weight per Piece (excluding packing)	6.000 g
Custom tariff number	85366990
Country of origin	Poland

## Technical data

#### Dimensions

Height	15 mm
Length	6 mm
Width	6 mm
Screw thread	M3

#### General

Color	red
Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm

**Environmental Product Compliance** 




# Female test connector - PSBJ 6-T RD - 3070319

### Technical data

### **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

# Drawings



## Classifications

eCl@ss

eCl@ss 10.0.1	27440313
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27440313
eCl@ss 8.0	27440313
eCl@ss 9.0	27440313

### ETIM

ETIM 4.0	EC000489
ETIM 5.0	EC002255
ETIM 6.0	EC002255
ETIM 7.0	EC002255

UNSPSC

UNSPSC 6.01 30211801
----------------------



# Female test connector - PSBJ 6-T RD - 3070319

### Classifications

#### UNSPSC

UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	20122006
UNSPSC 18.0	39121410
UNSPSC 19.0	39121410
UNSPSC 20.0	39121410
UNSPSC 21.0	39121410

### Accessories

#### Accessories

Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2component grip, with non-slip grip

Screwdriver - SF-SL 0,6X3,5-100 S-VDE - 1212587



Actuation tool, for ST terminal blocks, VDE insulated, with slimmer insulation integrated in the blade, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

Phoenix Contact 2020 © - all rights reserved http://www.phoenixcontact.com