

Insertion bridge - ESB 2-FK - 3131138


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Insertion bridge, pitch: 6.15 mm, length: 10.2 mm, width: 3 mm, number of positions: 2, color: gray

RoHS

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 093006
GTIN	4017918093006
Weight per Piece (excluding packing)	1.460 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Technical data

Color	gray
Material	PA66 V2
Number of positions	2
Pitch	6.15 mm
Length	10.2 mm
Height	24 mm
Width	3 mm
Flammability rating according to UL 94	PA66 V2

Standards and Regulations

Flammability rating according to UL 94	PA66 V2
--	---------

Insertion bridge - ESB 2-FK - 3131138

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27141140
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489
ETIM 6.0	EC000489
ETIM 7.0	EC000489

UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426
UNSPSC 18.0	39121426
UNSPSC 19.0	39121426
UNSPSC 20.0	39121426
UNSPSC 21.0	39121426