

Europe connectors - EC 16 - 3240179

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Polypropylene Europe terminal strip, white, for connecting solid conductors and stranded conductors with and without ferrules with a cross section of 1.5 to 16 mm²

Your advantages

- ✓ The polypropylene insulating housing enables individual positions to be disconnected simply by twisting and without the need for tools
- ✓ The high-quality metal parts, which feature corrosion-resistant surfaces, are fixed securely in the housing
- ✓ The prismatic clamping part facilitates conductor entry and reliable contact can be established even for conductors without ferrules

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 457842
GTIN	4046356457842
Weight per Piece (excluding packing)	7.400 g
Custom tariff number	85369010
Country of origin	Austria

Technical data

General

Number of positions	12
Number of levels	1
Number of connections	24
Nominal cross section	16 mm ²
Color	white
Insulating material	PP

Europe connectors - EC 16 - 3240179

Technical data

General

Flammability rating according to UL 94	-
Maximum load current	76 A (with 16 mm ² conductor cross section)
Nominal current I _N	76 A (with 16 mm ² conductor cross section)
Nominal voltage U _N	450 V
Open side panel	No
Ambient temperature (operation)	-40 °C ... 80 °C

Dimensions

Width	20.7 mm
Length	174.5 mm
Height	25 mm
Depth	20.7 mm
Drill hole spacing	15 mm
Pitch	15 mm

Connection data

Connection method	Screw connection
Screw thread	M4
Stripping length	8 mm
Tightening torque, min	1.2 Nm
Tightening torque max	1.5 Nm
Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	16 mm ²
Conductor cross section AWG min.	14
Conductor cross section AWG max.	6
Conductor cross section flexible min.	2.5 mm ²
Conductor cross section flexible max.	16 mm ²
Min. AWG conductor cross section, flexible	14
Max. AWG conductor cross section, flexible	6
Conductor cross section flexible, with ferrule without plastic sleeve min.	2.5 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	10 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve min.	2.5 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve max.	10 mm ²
2 conductors with same cross section, solid min.	2.5 mm ²
2 conductors with same cross section, solid max.	4 mm ²
2 conductors with same cross section, stranded min.	2.5 mm ²
2 conductors with same cross section, stranded max.	4 mm ²
Two conductors with the same cross section, flexible, with TWIN ferrules, with plastic sleeve, minimum	1 mm ²

Europe connectors - EC 16 - 3240179

Technical data

Connection data

Two conductors with the same cross section, flexible, with TWIN ferrules, with plastic sleeve, maximum	4 mm ²
Two conductors with the same cross section stranded, with ferrule and without plastic sleeve, minimum	1.5 mm ²
Two conductors with the same cross section stranded, with ferrule and without plastic sleeve, maximum	2.5 mm ²

Standards and Regulations

Flammability rating according to UL 94	-
--	---

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27141106
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141106
eCl@ss 8.0	27141106
eCl@ss 9.0	27141106

ETIM

ETIM 3.0	EC001284
ETIM 4.0	EC001284
ETIM 5.0	EC001284
ETIM 6.0	EC001284
ETIM 7.0	EC001284

UNSPSC

UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	39121409

Europe connectors - EC 16 - 3240179

Classifications

UNSPSC

UNSPSC 18.0	39121409
UNSPSC 19.0	39121409
UNSPSC 20.0	39121409
UNSPSC 21.0	39121409

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.BL08.B.00534
-----	---	--------------------------
