

Cable duct - CD-HF 25X80 - 3240343

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Cable duct for installation and mounting in control cabinets, light gray, halogen-free, comprising upper part and mounting base, width: 25 mm, height: 80 mm, length: 2000 mm

Your advantages

- Predetermined breaking point enables tool-free, burr-free removal of bars
- The wide, diagonal heads of the cable duct bars make it easy to fit the cover and hold it securely in place
- Fast and seamless creation of T and cross connections by means of an additional predetermined breaking point in the cable duct base
- Installed conductors are securely held in place by means of wire retaining clips that can be snapped onto bars on the side
- Cover is securely held in place for both horizontal and vertical mounting



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 046356 508285 |
| GTIN | 4046356508285 |
| Weight per Piece (excluding packing) | 1.000 g |
| Custom tariff number | 39259020 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------|---------|
| Length (b) | 2000 mm |
| Width (a) | 25 mm |
| Height (c) | 80 mm |

Ambient conditions

Cable duct - CD-HF 25X80 - 3240343

Technical data

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 90 °C |
|---------------------------------|------------------|

General

| | |
|--|----------------------|
| Color | light grey RAL 7035 |
| Components | halogen-free |
| Flammability rating according to UL 94 | V0 |
| Material | PC/ABS |
| Nominal cross section | 1202 mm ² |

Standards and Regulations

| | |
|--|-----|
| Halogen-free | yes |
| Connection in acc. with standard | CSA |
| Flammability rating according to UL 94 | V0 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Drawings

Cable duct - CD-HF 25X80 - 3240343

Dimensional drawing



Base perforation according to DIN EN 50085

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27400703 |
| eCl@ss 4.0 | 27140600 |
| eCl@ss 4.1 | 27140600 |
| eCl@ss 5.0 | 27140600 |
| eCl@ss 5.1 | 27140600 |
| eCl@ss 6.0 | 27400700 |
| eCl@ss 7.0 | 27400703 |
| eCl@ss 8.0 | 27400703 |
| eCl@ss 9.0 | 27400703 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000012 |
| ETIM 3.0 | EC000012 |

Cable duct - CD-HF 25X80 - 3240343

Classifications

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC000012 |
| ETIM 5.0 | EC000012 |
| ETIM 6.0 | EC000012 |
| ETIM 7.0 | EC000012 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30101815 |
| UNSPSC 7.0901 | 30101815 |
| UNSPSC 11 | 30101815 |
| UNSPSC 12.01 | 30101815 |
| UNSPSC 13.2 | 39131712 |
| UNSPSC 18.0 | 39131712 |
| UNSPSC 19.0 | 39131712 |
| UNSPSC 20.0 | 39131712 |
| UNSPSC 21.0 | 39131712 |

Approvals

Approvals

Approvals

CSA / UL Recognized / VDE Zeichengenehmigung

Ex Approvals

Approval details

| | | | |
|-----|--|---|--------|
| CSA | | http://www.csagroup.org/services-industries/product-listing/ | 248269 |
|-----|--|---|--------|

| | | | |
|---------------|--|---|---------------|
| UL Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 328576 |
|---------------|--|---|---------------|

Cable duct - CD-HF 25X80 - 3240343

Approvals

VDE Zeichengenehmigung



<http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx>

40028972

Accessories

Accessories

Cover

Cover profile - CD-HF COVER 25 - 3240369



Cover for cable duct, light gray, halogen-free, width: 25 mm, length: 2000 mm

Filler plug

Fastening clip - RVT-PA 4 - 3240498



Plastic body-bound rivet, for hole diameter of 4 mm and a material thickness of 1.5 ... 6 mm

Fastening clip - RVT-PA 6 - 3240499



Plastic body-bound rivet, for hole diameter of 6 mm and a material thickness of 1.5 ... 6 mm

Riveting tools

Cable duct - CD-HF 25X80 - 3240343

Accessories

Tool - UNIFOX-RVT P 4 - 1212478



Rivet setting tool, for use with RVT-PA 4 plastic body-bound rivets

Tool - UNIFOX-RVT P 6 - 1212509



Rivet setting tool, for use with RVT-PA 6 plastic body-bound rivets
