

Screw connection - WP-GR HF IP66 M20 BK - 3240954


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, metric thread, IP66 protection, with strain relief



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 20 pc |
| GTIN |  4 046356 710619 |
| GTIN | 4046356710619 |
| Weight per Piece (excluding packing) | 15.000 g |
| Custom tariff number | 39174000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------------|---------------------|
| Width (a) | 23 mm |
| Height (c) | 59 mm |
| Wrench size | 21 mm |
| Outside diameter | 15.8 mm |
| Cable diameter | 15.8 mm ... 15.8 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 115 °C |
| Degree of protection | IP66 |

General

Screw connection - WP-GR HF IP66 M20 BK - 3240954

Technical data

General

| | |
|--|--|
| Color | black |
| Type | With strain relief |
| | Outer thread |
| Components | free from silicone, halogen, and cadmium |
| Flammability rating according to UL 94 | V2 |
| Material | PA |

Standards and Regulations

| | |
|--|-----|
| Halogen-free | yes |
| Connection in acc. with standard | UL |
| Flammability rating according to UL 94 | V2 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27144432 |
| eCl@ss 4.0 | 27141200 |
| eCl@ss 4.1 | 27141200 |
| eCl@ss 5.0 | 27149100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27149100 |
| eCl@ss 7.0 | 27149109 |
| eCl@ss 8.0 | 27149109 |
| eCl@ss 9.0 | 27144432 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC001178 |
| ETIM 5.0 | EC001178 |
| ETIM 6.0 | EC000441 |
| ETIM 7.0 | EC000441 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211812 |
| UNSPSC 7.0901 | 39121410 |

Screw connection - WP-GR HF IP66 M20 BK - 3240954

Classifications

UNSPSC

| | |
|--------------|----------|
| UNSPSC 11 | 39121411 |
| UNSPSC 12.01 | 39121411 |
| UNSPSC 13.2 | 39121311 |
| UNSPSC 18.0 | 39121311 |
| UNSPSC 19.0 | 39121311 |
| UNSPSC 20.0 | 39121311 |
| UNSPSC 21.0 | 39121311 |

Approvals

Approvals

Approvals

LR / UL Recognized / VDE Zeichengenehmigung

Ex Approvals

Approval details

| | | |
|----|--|---|
| LR | | http://www.lr.org/en |
|----|--|---|

| | | |
|---------------|--|---|
| UL Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm |
|---------------|--|---|

| | | |
|------------------------|--|---|
| VDE Zeichengenehmigung | | http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx |
|------------------------|--|---|

Accessories

Accessories

Corrugated pipe

Screw connection - WP-GR HF IP66 M20 BK - 3240954

Accessories

Protective hose - WP-PA HF 15,8 BK - 3240682



Polyamide protective hose, inflammability class V0, UV resistant

Protective hose - WP-PA HF-HB 15,8 BK - 3240840



Polyamide protective hose, inflammability class HB, UV resistant
