

Screw connection - WP-GT PP HF PG11 - 3241004


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland made from PP with Pg thread, rotatable, IP54 protection



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 046356 711364 |
| GTIN | 4046356711364 |
| Weight per Piece (excluding packing) | 6.000 g |
| Custom tariff number | 39174000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------------|---------------------|
| Width (a) | 24.5 mm |
| Height (c) | 42 mm |
| Wrench size | 22 mm |
| Outside diameter | 17 mm |
| Cable diameter | 11.5 mm ... 11.5 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -10 °C ... 110 °C |
| Degree of protection | IP54 |

General

Screw connection - WP-GT PP HF PG11 - 3241004

Technical data

General

| | |
|--|--------------|
| Color | gray |
| Type | Rotatable |
| | Outer thread |
| Components | halogen-free |
| Flammability rating according to UL 94 | HB |
| Material | PP |

Standards and Regulations

| | |
|--|-----|
| Halogen-free | yes |
| Flammability rating according to UL 94 | HB |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27144432 |
| eCl@ss 4.0 | 27141200 |
| eCl@ss 4.1 | 27141200 |
| eCl@ss 5.0 | 27149100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27149100 |
| eCl@ss 7.0 | 27149109 |
| eCl@ss 8.0 | 27149109 |
| eCl@ss 9.0 | 27144432 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC001178 |
| ETIM 5.0 | EC001178 |
| ETIM 6.0 | EC000441 |
| ETIM 7.0 | EC000441 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121411 |

Screw connection - WP-GT PP HF PG11 - 3241004

Classifications

UNSPSC

| | |
|--------------|----------|
| UNSPSC 12.01 | 39121411 |
| UNSPSC 13.2 | 39121311 |
| UNSPSC 18.0 | 39121311 |
| UNSPSC 19.0 | 39121311 |
| UNSPSC 20.0 | 39121311 |
| UNSPSC 21.0 | 39121311 |

Approvals


Approvals

Approvals

VDE Zeichengenehmigung

Ex Approvals

Approval details

| | | |
|------------------------|---|---|
| VDE Zeichengenehmigung |  | http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx |
|------------------------|---|---|

Accessories

Accessories

Corrugated pipe

Protective hose - WP-SPIRAL PVC C 17 - 3240851



Protective hose, spring steel wire with PVC coating, highly stranded

Screw connection - WP-GT PP HF PG11 - 3241004

Accessories

Protective hose - WP-SPIRAL PU C HF 17 - 3240858



Protective hose, spring steel wire with PU coating, highly stranded