

## Screw connection - WP-G BRASS IP65 PG7 - 3241051


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland made from brass with Pg thread, IP65 protection



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 046356 712019
GTIN	4046356712019
Weight per Piece (excluding packing)	14.000 g
Custom tariff number	74122000
Country of origin	Germany

### Technical data

#### Dimensions

Length (b)	28 mm
Width (a)	19 mm
Height (c)	28 mm
Wrench size	15 mm
Inner diameter (f)	6 mm
Outside diameter	10 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
Degree of protection	IP65

# Screw connection - WP-G BRASS IP65 PG7 - 3241051

## Technical data

### General

Color	brass
Type	Straight
	Outer thread
Components	halogen-free
Material	Brass

## Classifications

### eCl@ss

eCl@ss 10.0.1	27430310
eCl@ss 4.0	27141200
eCl@ss 4.1	27141200
eCl@ss 5.0	21132000
eCl@ss 5.1	21132000
eCl@ss 6.0	21132000
eCl@ss 7.0	27439203
eCl@ss 8.0	27439203
eCl@ss 9.0	27430310

### ETIM

ETIM 3.0	EC000519
ETIM 4.0	EC000519
ETIM 5.0	EC001180
ETIM 6.0	EC001180
ETIM 7.0	EC001180

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	40141734
UNSPSC 18.0	40141734
UNSPSC 19.0	40141734
UNSPSC 20.0	40141734
UNSPSC 21.0	40141734

## Screw connection - WP-G BRASS IP65 PG7 - 3241051

### Approvals

#### Approvals

---

#### Approvals

VDE Zeichengenehmigung

---

#### Ex Approvals

---

### Approval details

VDE Zeichengenehmigung



<http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx>

### Accessories

#### Accessories

#### Corrugated pipe

Protective hose - WP-STEEL PVC C 10 - 3240867



Galvanized steel protective hose with PVC coating

---