


Cable driller - WG-D HF 16 - 3241105

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Cable drillers, for fast and tool-free bundling of conductors and cables, removable and reusable



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 500 pc |
| GTIN |  4 046356 717342 |
| GTIN | 4046356717342 |
| Weight per Piece (excluding packing) | 0.600 g |
| Custom tariff number | 39269097 |
| Country of origin | Taiwan |

Technical data

Dimensions

| | |
|----------------|-------------------|
| Length (b) | 34.5 mm |
| Width (a) | 16 mm |
| Cable diameter | 13.5 mm ... 16 mm |

Ambient conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (assembly) | -10 °C ... 60 °C |
| Optimum ambient temperature (storage/transport) | 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal |

Cable driller - WG-D HF 16 - 3241105

Technical data

Ambient conditions

| | |
|--|---|
| | properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat. |
|--|---|

General

| | |
|--|--------------------------------|
| Color | transparent |
| Type | Notched strip |
| Components | free from silicone and halogen |
| Flammability rating according to UL 94 | V2 |
| Material | PA 6.6 |
| Tensile strength | 0 N |

Standards and Regulations

| | |
|--|----|
| Resistance to UV radiation | no |
| Flammability rating according to UL 94 | V2 |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27140702 |
| eCl@ss 4.0 | 27140700 |
| eCl@ss 4.1 | 27140700 |
| eCl@ss 5.0 | 24210600 |
| eCl@ss 5.1 | 24210600 |
| eCl@ss 6.0 | 24210600 |
| eCl@ss 7.0 | 24210690 |
| eCl@ss 8.0 | 24210690 |
| eCl@ss 9.0 | 27140702 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000046 |
| ETIM 4.0 | EC000046 |
| ETIM 5.0 | EC000046 |
| ETIM 6.0 | EC000046 |
| ETIM 7.0 | EC000046 |

Cable driller - WG-D HF 16 - 3241105

Classifications

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30212109 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11 | 27121703 |
| UNSPSC 12.01 | 27121703 |
| UNSPSC 13.2 | 27121703 |
| UNSPSC 18.0 | 39121731 |
| UNSPSC 19.0 | 39121731 |
| UNSPSC 20.0 | 39121731 |
| UNSPSC 21.0 | 39121731 |