

Flat gasket - WP-FS HF IP68 M12 - 3241174

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Flat gasket, height: 1.6 mm, diameter: 20 mm, color: green



Your advantages

- The Centellen flat sealing rings are used to seal protective hose screw connections on uneven surfaces.
- IP68 degree of protection
- Resistant to oil, seal against dust and water, UV resistant, halogen-free, high mechanical stability

Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 50 pc |
| GTIN |  4 046356 785808 |
| GTIN | 4046356785808 |
| Weight per Piece (excluding packing) | 0.400 g |
| Custom tariff number | 68159900 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------------------|--------|
| Height (c) | 1.6 mm |
| Diameter | 20 mm |
| Inner diameter (f) | 12 mm |
| Material thickness (g) | 1.6 mm |

Ambient conditions

Flat gasket - WP-FS HF IP68 M12 - 3241174

Technical data

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -50 °C ... 200 °C |
| Degree of protection | IP68 |

General

| | |
|------------|--------------------------------|
| Color | green |
| Components | free from silicone and halogen |
| Material | Centellen |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27430319 |
| eCl@ss 4.0 | 27141200 |
| eCl@ss 4.1 | 27141200 |
| eCl@ss 5.0 | 21132000 |
| eCl@ss 5.1 | 21132000 |
| eCl@ss 6.0 | 21132000 |
| eCl@ss 7.0 | 27439218 |
| eCl@ss 8.0 | 27439218 |
| eCl@ss 9.0 | 27430319 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000519 |
| ETIM 4.0 | EC000519 |
| ETIM 5.0 | EC001181 |
| ETIM 6.0 | EC001181 |
| ETIM 7.0 | EC001181 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211812 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121411 |
| UNSPSC 12.01 | 39121411 |
| UNSPSC 13.2 | 39131608 |
| UNSPSC 18.0 | 39131608 |

Flat gasket - WP-FS HF IP68 M12 - 3241174

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 19.0 | 39131608 |
| UNSPSC 20.0 | 39131608 |
| UNSPSC 21.0 | 39131608 |