

## Switching lock - S-MT - 3247954

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Switching lock, length: 10.5 mm, width: 3.5 mm, height: 23.1 mm, color: white

### Your advantages

- Can be used in all ...-MT knife disconnect terminal blocks from the CLIPLINE complete system
- The optional switching lock snaps in and effectively prevents unintentional switching

### Key Commercial Data

|                                      |                     |
|--------------------------------------|---------------------|
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 50 pc               |
| GTIN                                 | <br>4 046356 587471 |
| GTIN                                 | 4046356587471       |
| Weight per Piece (excluding packing) | 0.400 g             |
| Custom tariff number                 | 85389099            |
| Country of origin                    | China               |

### Technical data

#### Technical data

|   |  |
|---|--|
| Color                                   | white  |
| Material                                | PA   |
| Length                                  | 10.5 mm  |
| Height                                  | 23.1 mm  |
| Width                                   | 3.5 mm   |
| Ambient temperature (operation)         | -60 °C ... 85 °C   |
| Ambient temperature (storage/transport) | -25 °C ... 55 °C (For a short time, not exceeding 24 h, -60 to +70 °C) |

# Switching lock - S-MT - 3247954

## Technical data

### Technical data

|  |   |
|--|---|
| Additional text                        | For a short time, not exceeding 24 h, -60 to +70 °C |
| Ambient temperature (assembly)         | -5 °C ... 70 °C                                     |
| Ambient temperature (actuation)        | -5 °C ... 70 °C                                     |
| Flammability rating according to UL 94 | V2  |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27141190 |
| eCl@ss 4.0    | 27141100 |
| eCl@ss 4.1    | 27141100 |
| eCl@ss 5.0    | 27141100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27141100 |
| eCl@ss 7.0    | 27141190 |
| eCl@ss 8.0    | 27141190 |
| eCl@ss 9.0    | 27141190 |

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC001287 |
| ETIM 5.0 | EC002848 |
| ETIM 6.0 | EC002848 |
| ETIM 7.0 | EC002848 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121421 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |
| UNSPSC 18.0   | 39121410 |
| UNSPSC 19.0   | 39121410 |

# Switching lock - S-MT - 3247954

## Classifications

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 20.0 | 39121410 |
| UNSPSC 21.0 | 39121410 |