


## Insert strip - ES-SSMK-GB 96X30 - 5032455

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Insert strip, Sheet, transparent/white, unlabeled, can be labeled with: Office printing systems, CMS-P1-PLOTTER, mounting type: insert, lettering field size: 92 x 26 mm, Number of individual labels: 22



### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| Minimum order quantity               | 10 pc   |
| GTIN                                 | <br>4 017918 095826 |
| GTIN                                 | 4017918095826   |
| Weight per Piece (excluding packing) | 10.550 g  |
| Custom tariff number                 | 48025890  |
| Country of origin                    | Germany   |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 30 mm |
| Width (a)  | 96 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 115 °C |
|---------------------------------|-------------------|

#### General

|                       |   |
|-----------------------|---|
| Note                  | Print image may vary depending on laser printer |
| Color                 | transparent/white                               |
| Base element material | Cardboard                                       |
| Components            | free from silicone and halogen                  |

# Insert strip - ES-SSMK-GB 96X30 - 5032455

## Technical data

### General

|  |        |
|--|--------|
| Flammability rating according to UL 94 | V2     |
| Number of individual labels            | 22     |
| Number of individual labels per row    | 2      |
| Marking mounting type                  | insert |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 4.0    | 24190200 |
| eCl@ss 4.1    | 24190200 |
| eCl@ss 5.0    | 27149100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27149100 |
| eCl@ss 7.0    | 27149129 |
| eCl@ss 8.0    | 27149129 |
| eCl@ss 9.0    | 27400629 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131504 |
| UNSPSC 18.0   | 39131504 |
| UNSPSC 19.0   | 39131504 |
| UNSPSC 20.0   | 39131504 |

## Insert strip - ES-SSMK-GB 96X30 - 5032455

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131504 |
|-------------|----------|