

Female test connector - PSBJ 4/15/6 RD - 0303325

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Female test connector, color: red

Your advantages

- ✓ The test socket PSBJ... is used in place of the normal bridge screw and ensures the voltage pick-off on a bridged group of terminals
- ✓ The test sockets are tailored to the special applications encountered in the power supply industry



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 000431
GTIN	4017918000431
Weight per Piece (excluding packing)	3.750 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

General

Color	red
-------	-----

Dimensions

Length	6 mm
Width	6 mm
Pin diameter	4 mm


Female test connector - PSBJ 4/15/6 RD - 0303325

Technical data

Material	Brass
Ambient conditions	
Operating temperature	-40 °C ... 80 °C
Environmental Product Compliance	
REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 10.0.1	27440313
eCl@ss 11.0	27440313
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27440313
eCl@ss 9.0	27440313

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002255
ETIM 6.0	EC002255
ETIM 7.0	EC002255

UNSPSC

UNSPSC 6.01	30211812
-------------	----------

Female test connector - PSBJ 4/15/6 RD - 0303325

Classifications

UNSPSC

UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121410
UNSPSC 18.0	39121410
UNSPSC 19.0	39121410
UNSPSC 20.0	39121410
UNSPSC 21.0	39121410