



Conductor marker - UCT-WMT (12X4) GN CUS - 0801527

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Conductor marker, can be ordered: by sheet, green, labeled according to customer specifications, mounting type: insert, cable diameter range: 0.6 ... 10 mm, lettering field size: 12 x 4 mm, Number of individual labels: 50



Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 |
| GTIN |  4 046356 682725 |
| GTIN | 4046356682725 |
| Custom tariff number | 49119900 |

Technical data

Dimensions

| | |
|----------------|------------------|
| Length (b) | 4 mm |
| Width (a) | 12 mm |
| Cable diameter | 0.6 mm ... 10 mm |

Ambient conditions

| | |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 120 °C |
| Recommended storage conditions | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

General

| | |
|-----------------|--------------------------------|
| Color | green |
| Components | free from silicone and halogen |
| Material | PC V0 |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |

Conductor marker - UCT-WMT (12X4) GN CUS - 0801527

Technical data

General

| | |
|-------------------------------------|-------------|
| Number of individual labels | 50 |
| Number of individual labels per row | 10 |
| Marking mounting type | insert |
| R22 | HL 1 - HL 3 |
| R23 | HL 1 - HL 3 |
| R24 | HL 1 - HL 3 |

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 11.0 | 27281102 |
| eCl@ss 4.0 | 27061700 |
| eCl@ss 4.1 | 27061700 |
| eCl@ss 5.0 | 27400400 |
| eCl@ss 5.1 | 27400400 |
| eCl@ss 6.0 | 27400400 |
| eCl@ss 7.0 | 27400401 |
| eCl@ss 9.0 | 27400629 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC001530 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39131504 |
| UNSPSC 18.0 | 39131504 |
| UNSPSC 19.0 | 39131504 |
| UNSPSC 20.0 | 39131504 |

Conductor marker - UCT-WMT (12X4) GN CUS - 0801527

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39131504 |
|-------------|----------|