

Engraving material - GPE 60X12 SR/R - 0806631

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Engraving material, Sheet, silver, unlabeled, can be labeled with: PLOTMARK, ENGRAVING UNIT, CMS-P1-PLOTTER, P1 ENGRAVING UNIT, mounting type: adhesive, lettering field size: 60 x 12 mm, Number of individual labels: 21

Your advantages

- ✔ Can be labeled easily using the CMS-P1-PLOTTER
- ✔ Can be engraved using the P1 ENGRAVING UNIT
- ✔ The adhesive foil used ensures good adhesive properties, even on uneven surfaces
- ✔ Labeling service: Phoenix Contact can custom-label all GPE ... markers according to your requirements
- ✔ Two-layer material
- ✔ The label sheet consists of prefabricated, individual self-adhesive labels



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 10 pc |
| GTIN |  4 017918 145040 |
| GTIN | 4017918145040 |
| Weight per Piece (excluding packing) | 18.900 g |
| Custom tariff number | 39203000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------|-------|
| Length (b) | 12 mm |
| Width (a) | 60 mm |
| Height (c) | 12 mm |

Engraving material - GPE 60X12 SR/R - 0806631

Technical data

Ambient conditions


| | |
|---------------------------------|---|
| Ambient temperature (operation) | -20 °C ... 85 °C |
| Recommended storage conditions | 20°C/50% relative humidity. Storage in the original packaging is recommended. |

General

| | |
|-------------------------------------|--------------------------------|
| Note | Can be labeled with CMS |
| Color | silver |
| Components | free from silicone and halogen |
| Material | TRANSPLY-ABS |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 21 |
| Number of individual labels per row | 7 |
| Marking mounting type | adhesive |

Drawings

Dimensional drawing



Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 11.0 | 27281103 |
| eCl@ss 4.0 | 24190200 |
| eCl@ss 4.1 | 24190200 |
| eCl@ss 5.0 | 27149100 |
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27149100 |
| eCl@ss 7.0 | 27149129 |
| eCl@ss 9.0 | 27400629 |

Engraving material - GPE 60X12 SR/R - 0806631

Classifications

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39131504 |
| UNSPSC 18.0 | 39131504 |
| UNSPSC 19.0 | 39131504 |
| UNSPSC 20.0 | 39131504 |
| UNSPSC 21.0 | 39131504 |