


## Label sheet, DIN A4 - ES-SSMK-GB 60X18 CUS - 0824408

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Label sheet, DIN A4, can be ordered: Sheet, transparent/white, labeled according to customer specifications, mounting type: insert, lettering field size: 56 x 14 mm



### Key Commercial Data

Packing unit	1
GTIN	 4 046356 352796
GTIN	4046356352796
Custom tariff number	49119900

### Technical data

#### Dimensions

Length (b)	18 mm
Width (a)	60 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 115 °C
---------------------------------	-------------------

#### General

Color	transparent/white
Base element material	PC
Components	free from silicone and halogen
Material	PC
Marking mounting type	insert

### Standards and Regulations

## Label sheet, DIN A4 - ES-SSMK-GB 60X18 CUS - 0824408

### Technical data

#### Standards and Regulations

Flammability rating according to UL 94	V2
--	----

### Classifications

#### eCl@ss

eCl@ss 10.0.1	27400629
eCl@ss 11.0	27281103
eCl@ss 4.0	24190200
eCl@ss 4.1	24190200
eCl@ss 5.0	27149100
eCl@ss 5.1	27141100
eCl@ss 6.0	27149100
eCl@ss 7.0	27149129
eCl@ss 9.0	27400629

#### ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761
ETIM 6.0	EC001288
ETIM 7.0	EC001288

#### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504