


## Engraving material - GPE 20X 8 WH CUS - 0824417

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Engraving material, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 mm x 8 mm, Number of individual labels: 88




### Your advantages

- Can be engraved using the P1 ENGRAVING UNIT
- Can be labeled easily using the CMS-P1-PLOTTER
- The adhesive foil used ensures good adhesive properties, even on uneven surfaces
- Labeling service: Phoenix Contact can custom-label all GPE ... markers according to your requirements
- Two-layer material
- The label sheet consists of prefabricated, individual self-adhesive labels



### Key Commercial Data

|                      |   |
|----------------------|---|
| Packing unit         | 1   |
| GTIN                 | <br>4 046356 352871 |
| GTIN                 | 4046356352871   |
| Custom tariff number | 39203000  |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 8 mm  |
| Width (a)  | 20 mm |

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -20 °C ... 85 °C  |
| Recommended storage conditions  | 20°C/50% relative humidity. Storage in the original packaging is recommended. |

## Engraving material - GPE 20X 8 WH CUS - 0824417

### Technical data

#### General

|                                     |                                |
|-------------------------------------|--------------------------------|
| Color                               | white                          |
| Components                          | free from silicone and halogen |
| Material                            | TRANSPLY-ABS                   |
| Wipe resistance                     | DIN EN 61010-1 (VDE 0411-1)    |
| Number of individual labels         | 88                             |
| Number of individual labels per row | 4                              |
| Marking mounting type               | adhesive                       |

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 11.0   | 27281103 |
| eCl@ss 4.0    | 24190200 |
| eCl@ss 4.1    | 24190200 |
| eCl@ss 5.0    | 27141100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27141100 |
| eCl@ss 7.0    | 27141137 |
| eCl@ss 9.0    | 27400629 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131505 |
| UNSPSC 18.0   | 39131504 |
| UNSPSC 19.0   | 39131504 |
| UNSPSC 20.0   | 39131504 |
| UNSPSC 21.0   | 39131504 |

