

Contactormarker - SS-3R 20X7 WH CUS - 0824467


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contactormarker, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snapped into marker carrier, for terminal block width: 20 mm, lettering field size: 20 x 7 mm



Key Commercial Data

Packing unit	1
GTIN	 4 046356 355186
GTIN	4046356355186
Custom tariff number	49119900

Technical data

Dimensions

Length (b)	20 mm
Width (a)	7 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

General

Color	white
Base element material	ABS
Type	high
Material	ABS
Wipe resistance	DIN 30646
	DIN VDE 0611-1
Marking mounting type	snapped into marker carrier

Contactor marker - SS-3R 20X7 WH CUS - 0824467

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 10.0.1	27141137
eCl@ss 11.0	27281101
eCl@ss 4.0	24190200
eCl@ss 4.1	24190200
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141137
eCl@ss 9.0	27141137

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC000761
ETIM 6.0	EC000761
ETIM 7.0	EC000761

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131505
UNSPSC 18.0	39131505
UNSPSC 19.0	39131505
UNSPSC 20.0	39131505
UNSPSC 21.0	39131505