**PHŒNIX CONTACT**

# Marker for terminal blocks - UC1-TMF 6 CUS - 0824517

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.45 x 5.2 mm, Number of individual labels: 80

## Your advantages

☑ The UC1-TMF ... UniCard labeling range includes markers for Weidmüller, Wago, ABB (entrelec), Conta-Clip, and Klemsan terminal blocks

☑ Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements

☑ The markers, which are supplied in uniform sheets, can be labeled quickly and easily using the BLUEMARK LED

☑ The multi-section marking strips are easy to fit and can be easily separated if required

☑ The markers support multi-line labeling

☑ The sheets provide space for including function texts

**RoHS**

PRINTED FOR YOU

## Key Commercial Data

| Packing unit | 1 pc |
|---|---|
| GTIN | 4 046356 356398 |
| GTIN | 4046356356398 |
| Weight per Piece (excluding packing) | 8.700 g |
| Custom tariff number | 49119900 |
| Country of origin | Poland |

## Technical data

### Dimensions

| Width (a) | 6 mm |
|---|---|

### Ambient conditions

| Ambient temperature (operation) | -40 °C ... 120 °C |
|---|---|

# Marker for terminal blocks - UC1-TMF 6 CUS - 0824517

## Technical data

### General

| Color | white |
|---|---|
| Type | flat |
| Components | free from silicone and halogen |
| Material | PA |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 80 |
| Number of individual labels per row | 10 |
| Marking mounting type | snap into flat marker groove |
| R22 | HL 1 - HL 2 |
| R23 | HL 1 - HL 2 |
| R24 | HL 1 - HL 2 |

### Standards and Regulations

| Flammability rating according to UL 94 | V2 |
|---|---|

## Drawings

Schematic diagram

① Horizontal
② Vertical

## Classifications

### eCl@ss

| eCl@ss 10.0.1 | 27141137 |
|---|---|
| eCl@ss 11.0 | 27281101 |
| eCl@ss 4.0 | 24190200 |
| eCl@ss 4.1 | 24190200 |

# Marker for terminal blocks - UC1-TMF 6 CUS - 0824517

## Classifications

### eCl@ss

| eCl@ss 5.0 | 27141100 |
|------------|----------|
| eCl@ss 5.1 | 27141100 |
| eCl@ss 6.0 | 27141100 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 9.0 | 27141137 |

### ETIM

| ETIM 2.0 | EC000761 |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 6.0 | EC000761 |
| ETIM 7.0 | EC000761 |

### UNSPSC

| UNSPSC 6.01 | 30211811 |
|-------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39131505 |
| UNSPSC 18.0 | 39131505 |
| UNSPSC 19.0 | 39131505 |
| UNSPSC 20.0 | 39131505 |
| UNSPSC 21.0 | 39131505 |