


## Plastic label - UC-EMLP (20X8) YE CUS - 0824557

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plastic label, can be ordered: by sheet, yellow, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 mm x 8 mm




### Your advantages

- All UC-EMLP ... self-adhesive device markers can also be supplied labeled according to customer requirements



### Key Commercial Data

|                      |   |
|----------------------|---|
| Packing unit         | 1   |
| GTIN                 | <br>4 046356 356763 |
| GTIN                 | 4046356356763   |
| Custom tariff number | 49119900  |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 8 mm  |
| Width (a)  | 20 mm |

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 120 °C   |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

#### General

|            |                                |
|------------|--------------------------------|
| Color      | yellow                         |
| Components | free from silicone and halogen |
| Material   | PA                             |

# Plastic label - UC-EMLP (20X8) YE CUS - 0824557

## Technical data

### General

|                                     |                             |
|-------------------------------------|-----------------------------|
| Wipe resistance                     | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels per row | 2                           |
| Marking mounting type               | adhesive                    |
| R22                                 | HL 1 - HL 2                 |
| R23                                 | HL 1 - HL 2                 |
| R24                                 | HL 1 - HL 2                 |

### Standards and Regulations

|  |    |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 11.0   | 27281103 |
| eCl@ss 4.0    | 24190200 |
| eCl@ss 4.1    | 24190200 |
| eCl@ss 5.0    | 27149100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27149100 |
| eCl@ss 7.0    | 27149129 |
| eCl@ss 9.0    | 27400629 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131504 |
| UNSPSC 18.0   | 39131504 |
| UNSPSC 19.0   | 39131504 |

## Plastic label - UC-EMLP (20X8) YE CUS - 0824557

### Classifications

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 20.0 | 39131504 |
| UNSPSC 21.0 | 39131504 |