

## Cable marker - WMT 2,4 (15X4)R CUS - 0824927

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Cable marker, can be ordered: by line, white, labeled according to customer specifications, mounting type: insert, cable diameter range: 1 ... 2.4 mm, lettering field size: 15 x 4 mm

### Your advantages

- ✓ High-quality labeling image created by thermal transfer printing
- ✓ Available for different conductor diameters
- ✓ The special hole geometry ensures a strong axial hold
- ✓ Made from high-quality polyester foil
- ✓ Custom labeling and easy handling
- ✓ Labeling service: Phoenix Contact can custom-label all conductor markers according to your requirements
- ✓ Special packaging protects the conductor markers against external influences, dust, and dirt
- ✓ The conductor to be marked is threaded through two punched holes in the marker and positioned



### Key Commercial Data

Packing unit	1
GTIN	 4 046356 358804
GTIN	4046356358804
Custom tariff number	49119900

### Technical data

#### Dimensions

Length (b)	29.3 mm
Width (a)	4.2 mm
Cable diameter	1 mm ... 2.4 mm

# Cable marker - WMT 2,4 (15X4)R CUS - 0824927

## Technical data

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C / 50 % relative humidity

### General

Color	white
Type	Roll
Components	free from silicone and halogen
Material	Polyester
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels per row	3
Marking mounting type	insert

### Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

## Classifications

### eCl@ss

eCl@ss 10.0.1	27400401
eCl@ss 11.0	27281102
eCl@ss 4.0	27061700
eCl@ss 4.1	27061700
eCl@ss 5.0	27400400
eCl@ss 5.1	27400400
eCl@ss 6.0	27400400
eCl@ss 7.0	27400401
eCl@ss 9.0	27400401

### ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 6.0	EC001530
ETIM 7.0	EC001530

### UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410

## Cable marker - WMT 2,4 (15X4)R CUS - 0824927

### Classifications

#### UNSPSC

UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504