


## Snap-in markers - UC-EM (18X8) CUS - 0827627

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Snap-in markers, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snapped into marker carrier, lettering field size: 18 x 8 mm, Number of individual labels: 20



### Key Commercial Data

|                      |   |
|----------------------|---|
| Packing unit         | 1   |
| GTIN                 | <br>4 046356 447720 |
| GTIN                 | 4046356447720   |
| Custom tariff number | 49119900  |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 8 mm  |
| Width (a)  | 18 mm |

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 120 °C   |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

#### General

|                             |                                |
|-----------------------------|--------------------------------|
| Color                       | white                          |
| Components                  | free from silicone and halogen |
| Material                    | PA                             |
| Wipe resistance             | DIN EN 61010-1 (VDE 0411-1)    |
| Number of individual labels | 20                             |

# Snap-in markers - UC-EM (18X8) CUS - 0827627

## Technical data

### General

|                                     |                             |
|-------------------------------------|-----------------------------|
| Number of individual labels per row | 5                           |
| Marking mounting type               | snapped into marker carrier |
| R22                                 | HL 1 - HL 2                 |
| R23                                 | HL 1 - HL 2                 |
| R24                                 | HL 1 - HL 2                 |

### Standards and Regulations


|  |    |
|--|----|
| Flammability rating according to UL 94 | V2 |
|--|----|

### Environmental Product Compliance

|            |   |
|------------|---|
| China RoHS | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |
|------------|---|

## Drawings

Pictogram



## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 11.0   | 27281103 |
| eCl@ss 4.0    | 24190200 |
| eCl@ss 4.1    | 24190200 |
| eCl@ss 5.0    | 27141100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27141100 |
| eCl@ss 7.0    | 27141137 |
| eCl@ss 9.0    | 27400629 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

## Snap-in markers - UC-EM (18X8) CUS - 0827627

### Classifications

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39131505 |
| UNSPSC 18.0   | 39131504 |
| UNSPSC 19.0   | 39131504 |
| UNSPSC 20.0   | 39131504 |
| UNSPSC 21.0   | 39131504 |