

Aluminum label - WMTB-AL (29X8) CUS - 0830807

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Aluminum label, can be ordered: Piece, aluminum color, labeled according to customer specifications, mounting type: Assembly with cable binders, cable diameter: > 2.9 mm, lettering field size: 29 x 8 mm

Your advantages

- Aluminum cable marking for assembly with cable binders
- High-quality appearance
- Suitable for large-surface marking of conductors and cables > 2.9 mm in diameter



Key Commercial Data

Packing unit	1
GTIN	 4 046356 780834
GTIN	4046356780834
Custom tariff number	76169990

Technical data

Dimensions

Length (b)	48 mm
Width (a)	8 mm

Ambient conditions

Recommended storage conditions	5 °C ... 25 °C
--------------------------------	----------------

General

Color	aluminum color
Type	Roll
Components	free from silicone, halogen, and cadmium

Aluminum label - WMTB-AL (29X8) CUS - 0830807

Technical data

General

Material	Aluminum
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Marking mounting type	Assembly with cable binders
Min. cross section	6 mm ²

Classifications

eCl@ss

eCl@ss 10.0.1	27400401
eCl@ss 11.0	27281102
eCl@ss 4.0	27061700
eCl@ss 4.1	27061700
eCl@ss 5.0	27400400
eCl@ss 5.1	27400400
eCl@ss 6.0	27400400
eCl@ss 7.0	27400401
eCl@ss 9.0	27400401

ETIM

ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 6.0	EC001530
ETIM 7.0	EC001530

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504