

## Cable marker - LS-WMTB-AL (29X8) - 0831500

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Cable marker, Aluminum label, aluminum color, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: Assembly with cable binders, cable diameter: > 2.9 mm, lettering field size: 29 x 8 mm, Number of individual labels: 36



### Your advantages

- Aluminum cable marking for assembly with cable binders
- High-quality appearance
- Suitable for large-surface marking of conductors and cables > 2.9 mm in diameter



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
GTIN	 4 046356 924740
GTIN	4046356924740
Weight per Piece (excluding packing)	68.000 g
Custom tariff number	76169990
Country of origin	China

### Technical data

#### Dimensions

Length (b)	47 mm
Width (a)	8.5 mm
Material thickness (g)	0.80 mm

#### Ambient conditions

## Cable marker - LS-WMTB-AL (29X8) - 0831500

### Technical data

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 120 °C (At temperatures above 80 °C there might be a slight change to the material surface)
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

#### General

Color	aluminum color
Type	Card form
Components	free from silicone, halogen, and cadmium
Material	Aluminum
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	36
Marking mounting type	Assembly with cable binders

### Classifications

#### eCl@ss

eCl@ss 10.0.1	27400401
eCl@ss 11.0	27281102
eCl@ss 4.0	27061700
eCl@ss 4.1	27061700
eCl@ss 5.0	27400400
eCl@ss 5.1	27400400
eCl@ss 6.0	27400400
eCl@ss 7.0	27400401
eCl@ss 9.0	27400401

#### ETIM

ETIM 4.0	EC001530
ETIM 6.0	EC001530
ETIM 7.0	EC001530

#### UNSPSC

UNSPSC 13.2	39131504
UNSPSC 18.0	39131504
UNSPSC 19.0	39131504
UNSPSC 20.0	39131504
UNSPSC 21.0	39131504

## Cable marker - LS-WMTB-AL (29X8) - 0831500

### Accessories

#### Accessories

#### Cable tie

Cable tie - WT-STEEL SH 4,6X150 - 3240820



Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

---

Cable tie - WT-STEEL S 4,6X150 - 3240807



Cable binders, made from rust-free stainless steel (AISI 304), suitable for harsh ambient conditions, with ball lock, for quick and secure bundling and fastening

---

Cable tie - WT-HF 4,5X160 BK - 3240757



Cable binders for quick and secure bundling, standard version

---

Cable tie - WT-UV HF 4,5X200 BK - 3240834



Cable binders for quick and permanent fastening, UV-resistant and weatherproof (ISO 4892\_QUV-B 600 h)

---

Cable tie - WT-HT HF 4,5X200 BK - 3240787



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

## Cable marker - LS-WMTB-AL (29X8) - 0831500

### Accessories

---

Cable tie - WT-HT HF 4,5X200 - 3240786



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

---

Cable tie - WT-HP HF 4,5X290 - 0830984



Cable binders for quick and secure bundling, standard version

---

Cable tie - WT-ID HF 4,5X200 BU - 3240797



Cable binders for quick and secure fastening, can be detected using metallic pigments

---

Cable tie - WT-HF 4,5X160 - 3240756



Cable binders for quick and secure bundling, standard version

---

### Magazine

Magazine - TOPMARK LASER-MAG SHEET - 0831836

Sheet magazine for TOPMARK LASER



## Cable marker - LS-WMTB-AL (29X8) - 0831500

### Accessories

#### Printing system

Laser marker - TOPMARK NEO SET - 1012018



Laser marker incl. extraction unit with operating instructions, declaration of conformity, LS adapter plate +4 magnets, LS retaining plate, power cables: type E and F, LAN cable, D-SUB cable 25-pos., suction tube, crevice nozzle set and filter equipment

---

#### Printing system accessories

Adapter plate - TMN-ADAPTER PLATE-LS - 1012104



Adapter plate, for LS materials, for TOPMARK NEO, weight: 0.193 kg