

Cable marker - LS-WMTB-AL (29X8) BK - 0831508

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Cable marker, Aluminum label, black, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, mounting type: Assembly with cable binders, cable diameter: > 2.9 mm, lettering field size: 29 x 8 mm, Number of individual labels: 36




Your advantages

- Aluminum cable marking for assembly with cable binders
- High-quality appearance
- Suitable for large-surface marking of conductors and cables > 2.9 mm in diameter



Key Commercial Data

| | |
|------------------------|---|
| Packing unit | 1 pc |
| Minimum order quantity | 5 pc |
| GTIN |  4 046356 925105 |
| GTIN | 4046356925105 |
| Custom tariff number | 76169990 |
| Country of origin | China |

Technical data

Dimensions

| | |
|------------------------|---------|
| Length (b) | 47 mm |
| Width (a) | 8.5 mm |
| Material thickness (g) | 0.80 mm |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -25 °C ... 70 °C |
|---------------------------------|------------------|

Cable marker - LS-WMTB-AL (29X8) BK - 0831508

Technical data

Ambient conditions

| | |
|--------------------------------|---|
| Recommended storage conditions | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |
|--------------------------------|---|

General

| | |
|-----------------------------|--|
| Color | black |
| Type | Card form |
| Components | free from silicone, halogen, and cadmium |
| Material | Aluminum |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 36 |
| Marking mounting type | Assembly with cable binders |

Classifications

eCl@ss

| | |
|---------------|----------|
| eCl@ss 10.0.1 | 27400401 |
| eCl@ss 11.0 | 27281102 |
| eCl@ss 4.0 | 27061700 |
| eCl@ss 4.1 | 27061700 |
| eCl@ss 5.0 | 27400400 |
| eCl@ss 5.1 | 27400400 |
| eCl@ss 6.0 | 27400400 |
| eCl@ss 7.0 | 27400401 |
| eCl@ss 9.0 | 27400401 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC001530 |
| ETIM 6.0 | EC001530 |
| ETIM 7.0 | EC001530 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 39131504 |
| UNSPSC 18.0 | 39131504 |
| UNSPSC 19.0 | 39131504 |
| UNSPSC 20.0 | 39131504 |
| UNSPSC 21.0 | 39131504 |

Cable marker - LS-WMTB-AL (29X8) BK - 0831508

Accessories

Accessories

Cable tie

Cable tie - WT-STEEL SH 4,6X150 - 3240820



Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

Cable tie - WT-STEEL S 4,6X150 - 3240807



Cable binders, made from rust-free stainless steel (AISI 304), suitable for harsh ambient conditions, with ball lock, for quick and secure bundling and fastening

Cable tie - WT-HF 4,5X160 BK - 3240757



Cable binders for quick and secure bundling, standard version

Cable tie - WT-UV HF 4,5X200 BK - 3240834



Cable binders for quick and permanent fastening, UV-resistant and weatherproof (ISO 4892_QUV-B 600 h)

Cable tie - WT-HT HF 4,5X200 BK - 3240787



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

Cable marker - LS-WMTB-AL (29X8) BK - 0831508

Accessories

Cable tie - WT-HT HF 4,5X200 - 3240786



Cable binders for quick and secure bundling, heat stabilized to 125°C (also up to 145°C for brief periods)

Cable tie - WT-HP HF 4,5X290 - 0830984



Cable binders for quick and secure bundling, standard version

Cable tie - WT-ID HF 4,5X200 BU - 3240797



Cable binders for quick and secure fastening, can be detected using metallic pigments

Cable tie - WT-HF 4,5X160 - 3240756



Cable binders for quick and secure bundling, standard version

Magazine

Magazine - TOPMARK LASER-MAG SHEET - 0831836

Sheet magazine for TOPMARK LASER



Cable marker - LS-WMTB-AL (29X8) BK - 0831508

Accessories

Printing system

Laser marker - TOPMARK NEO SET - 1012018



Laser marker incl. extraction unit with operating instructions, declaration of conformity, LS adapter plate +4 magnets, LS retaining plate, power cables: type E and F, LAN cable, D-SUB cable 25-pos., suction tube, crevice nozzle set and filter equipment

Printing system accessories

Adapter plate - TMN-ADAPTER PLATE-LS - 1012104



Adapter plate, for LS materials, for TOPMARK NEO, weight: 0.193 kg