


Coding star - PC - 3040588

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coding star, length: 3 mm, width: 3 mm, height: 6 mm, color: red

Your advantages

- Can be used in all terminal blocks, couplings, and PCB headers
- The individual coding elements are inserted at the coding position in the basic terminal block and the coding tab is removed at the corresponding point on the plug



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	50 pc
GTIN	 4 017918 832728
GTIN	4017918832728
Weight per Piece (excluding packing)	0.870 g
Custom tariff number	39269097
Country of origin	Poland

Technical data

General

Color	red
Insulating material	PA
Material	PC
Flammability rating according to UL 94	V0

Dimensions

Coding star - PC - 3040588

Technical data

Dimensions

Width	3 mm
Length	3 mm
Height	6 mm

Standards and Regulations

Flammability rating according to UL 94	V0
----------------------------------------	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27440203
eCl@ss 11.0	27440203
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27269200
eCl@ss 7.0	27440203
eCl@ss 9.0	27440203

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002498
ETIM 6.0	EC002311
ETIM 7.0	EC002311

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	27112301
UNSPSC 18.0	27112301
UNSPSC 19.0	27112301

Coding star - PC - 3040588

Classifications

UNSPSC

UNSPSC 20.0	27112301
UNSPSC 21.0	27112301