

AS-Interface accessory IP68 T-distributor U_ASi and Uaux for round cable 1 x M12 connector, 2 x M12 socket



General technical data		
Type of device		AS-Interface accessories
Design of the product		M12-T distribution board
Function		T distribution M12
Connections/Terminals		
connection		M12
Connection system		M12
AS interface		
• Connection		1 x M12 connector / 2 x M12 box
Inputs		
Inputs socket assignment		1 = AS-i "+" 2 = Uaux "-" 3=AS-i "-" 4 = Uaux "+"
Mechanical data		
Type of mounting		screw fixing
Contacts Load rating max	A	4
Ambient conditions		
Ambient temperature	°C	-25 ... +85
Ambient temperature during storage	°C	-25 ... +85

degree of protection

IP68

Certificates/approvals

General Product Approval	EMC	Declaration of Conformity	Shipping Approval
--------------------------	-----	---------------------------	-------------------



EG-Konf.

[Miscellaneous](#)



ABS



PRS

Shipping Approval	other
-------------------	-------



RMRS

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1901-1TR00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-1TR00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-1TR00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-1TR00&lang=en

last modified:

09/13/2019